



# S29717

25T5/LED/46-835/BP/HO/120-277V  
 25 watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average  
 rated hours; 3200 lumens; 120-277 volts

## Features

- No ballast or external driver required
- All glass tube
- PET shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S29717

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S29717	045923297175	120-277	25	50/60Hz	T5	Miniature Bi-Pin	G5
Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
25T5/LED/46-835/BP/HO/120-277V	Frosted	48"	0.88"	3200	50000	3500	Neutral White
CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PL3RGVA3G1QP <a href="#">DLC Search</a>	Yes	Yes
UL Classification						Warranty	
cULus Classified - Damp Location Rated						<a href="#">5 Year Limited</a>	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

