

Project Name

Location

Prepared By



SATCO S39720

25T5/LED/46-865/BP/HO/SE-DE

Notes

[www] 05-15-2024 04:42:50

General

Status	Active
Watts	25W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frost
CCT (Kelvin)	6500K
Temperature	Daylight
CRI	83
Lumens	3400L
Beam Spread	180
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	46
MOD	0.83
Material	Aluminum
Lens Finish	Frost
Lens Material	Glass
Housing Color	Silver
Weight (lb.)	0.2

Additional Information

Tube Guard Use	Not Approved
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T5 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PILKXR6N
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale

RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

