

StackLight™

200 Class

70mm



Edwards 200 Class 70mm StackLight is a versatile signaling device that may contain up to five light modules, or four light modules with one sounder module in a single, integrated stack. The sounder module has been designed so that it is always in the top position.

The lens modules are available with LED, Incandescent or Xenon Strobe light sources. Options for steady-on, flashing or multi-mode are available. The lenses are made from a self-extinguishing polycarbonate material and are scratch and impact resistant.

Features and Specifications

- LED, Incandescent and Xenon Strobe light source
- Steady-on, flashing or multi-mode (flashing or steady-on)
- Interlocking system for quick assembly
- Available in gray or black
- Two optional NEMA Type 3R, IP54 rated sounders available:
 - Piezoelectric: 6 user selectable tones
 - Magnetodynamic: 32 user selectable tones
- Threaded footing must be ordered separately (not included with 270BC*)
- Additional mounting options available
- NEMA Type 4X rated
- IP66 rated base and light modules
- Operating temperature range: -22°F to 140°F (-30°C to 60°C)



Ordering Information

Description	Cat. No.*	Operating Temp.
Wiring Base and Cover - Gray	270BC¹	-22°F to 140°F (-30°C to 60°C)

Module Type	Cat. No.*	Operating Voltage ²	Current	Lens/LED Color	Operating Temp.
Gray Integrated LED Steady-on	270LEDSA24AD	24V AC	0.085 A	Amber	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LEDSR24AD	24V AC	0.085 A	Red	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LEDSY24AD	24V AC	0.085 A	Yellow	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LEDSB24AD	24V AC	0.075 A	Blue	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LED SG24AD	24V AC	0.075 A	Green	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LED SW24AD	24V AC	0.075 A	Clear/White	-22°F to 122°F (-30°C to 50°C)
		24V DC	0.065 A		
	270LEDSA120A	120V AC	0.035 A	Amber	-22°F to 122°F (-30°C to 50°C)
	270LEDSR120A	120V AC	0.035 A	Red	
	270LEDSY120A	120V AC	0.035 A	Yellow	
	270LEDSB120A	120V AC	0.035 A	Blue	
	270LED SG120A	120V AC	0.035 A	Green	
	270LED SW120A	120V AC	0.035 A	Clear/White	-22°F to 122°F (-30°C to 50°C)
	270LEDSA240A	240V AC	0.035 A	Amber	
	270LEDSR240A	240V AC	0.035 A	Red	
	270LEDSY240A	240V AC	0.035 A	Yellow	
	270LEDSB240A	240V AC	0.035 A	Blue	
	270LED SG240A	240V AC	0.035 A	Green	
	270LED SW240A	240V AC	0.035 A	Clear/White	

***NOTE: Add "B" to end of the catalog number for Black unit.**

¹Threaded footing (270THF) is not included. Order separately.

²AC voltage frequency is 50/60 Hz



StackLight™
200 Class
70mm

Accessories	
Description	Cat. No.
Junction Box - Gray	270JBX*
Footing with Extension - Gray	270KIT*
Threaded Extension Pole 100mm - Gray	270TEP*
Threaded Footing - Gray	270THF*
Threaded Wall Mount - Gray	270TWM*
Double Threaded Wall Mount - Gray	270TWM2*
270 Flexible Steel Extension Rod - 370mm	270FLXT
270 Stainless Steel Extension Rod - 100mm	270SSXT100
270 Stainless Steel Extension Rod - 200mm	270SSXT200
270 Stainless Steel Extension Rod - 400mm	270SSXT400

**NOTE: Add "B" to end of the catalog number for Black unit.*



Junction Box



Threaded Footing



Footing with Extension



Threaded Extension Pole



100mm
200mm
400mm

Stainless Steel
Extension Rod

370mm
Flexible Steel
Extension Rod



Threaded Wall Mount



Double Threaded Wall Mount