

3-3489

Wall Mount, Outdoor



Features

Housing

Die-formed Cold-rolled Steel with Powder Coated Finish
Finish Options: -05 Black, -06 White (GU24 CFL Type Only)

Optical

Shade: High Transmission Glass Create Excellent Light Distribution and Uniformity

Electrical

120V, Built-in Photo Cell Option

Lamp

Integrate LED Module: Color Temperature Option 3000K, 3500K, 4000K, 5000K
GU24 CFL Bulb Type: Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish	Dimension (H x W X E)	Energy Star
3-3489D-3000K	120V	15W	3000K / 80	1140	Oil Rubbed Bronze	10.0" x 10.0" x 5.4"	Yes
3-3489D-4000K	120V	15W	4000K / 80	1200	Oil Rubbed Bronze	10.0" x 10.0" x 5.4"	Yes

GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Shade	Dimension (H x W X E)	Energy Star
3-3489PG-05	120V	Black	2 x 13W GU24	Glass	10.0" x 10.0" x 5.4"	