

3-4001

Wall Mount, Outdoor



Features

Housing

Die-cast Aluminum with Powder Coated Finish
Finish Option: -06 White

Electrical

High Power Factor, Low THD
Built-in with or without Photo Cell

Lamp

Built-in LED Module: More Color Temperature Option 4000K, 5000K
GU24 Type: LED Bulb Color Temperature Option 3000K, 4000K
CFL Bulb Color Temperature Option 2700K, 4000K

Certification

UL/cUL or ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Warranty on LED Driver and Module



Built-in LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Shade	Dimension (H x W X E)	Energy Star
3-4001D-05-xxxxK	120V	13W	3000K / 80	580	Glass	14.0" x 6.5" x 7.2"	Yes
3-4001D-05-xxxxK-11W	120V	11W	3000K / 80	550	Glass	14.0" x 6.5" x 7.2"	Yes

GU24 Type

Model	Input Voltage	Input Wattage	Lamp	Finish/ Lumen(Typ)	Shade	Dimension (H x W X E)	Energy Star
3-4001PG-05	120V	18W	1 x 18W GU24	Black	Glass	14.0" x 6.5" x 7.2"	---