

3-4081

Wall Mount, Outdoor



Features

Housing

Die-cast Aluminum with Powder Coated Finish
 Finish Option: -06 White

Electrical

High Power Factor, Low THD

Lamp


Built-in LED Module: Color Temperature Option 3000K, 4000K, 5000K
 GU24 Type or E26 Type: LED Bulb Color Temperature Option 3000K, 4000K
 CFL Bulb Color Temperature Option 2700K, 4000K
 Photo Cell Option (Photo Shown with Photo Cell)

Certification

UL/cUL, ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Warranty on LED Driver and Module



Built-in LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Shade	Dimension (H x W X E)	Energy Star	Note
3-4081D-05-xxxxK	120V	14W	3000K / 80	1140	Glass	16.5" x 8.1" x 8.5"	Yes	---
3-4081D-05-xxxxK-11W	120V	11W	3000K / 80	770	Glass	16.5" x 8.1" x 8.5"	Yes	Driver on Board

GU24 Type

Model	Input Voltage	Input Wattage	Lamp	Finish / Lumen(Typ)	Shade	Dimension (H x W X E)	Energy Star
3-4081PG-05	120V	18W	1 x 18W GU24	Black	Glass	16.5" x 8.1" x 8.5"	---

E26 Type

Model	Input Voltage	Input Wattage	Lamp	Finish / Lumen(Typ)	Shade	Dimension (H x W X E)	Energy Star
3-4081-05	120V	9W	E26 LED Bulb	Black	Glass	16.5" x 8.1" x 8.5"	---

Order Code: -PC Photo Cell