

3-4310

Wall Mount / Ceiling Mount, Outdoor



Features

Housing

Die-Cast Aluminum with Powder Coated Finish or Stainless Steel

Finish Option: -06 White, -08 Gray, -03 Stainless Steel

Optical

Diffuser: Opal Polycarbonate

Electrical

120V, Built-in Photo Cell Option

Lamp

LED Type: Integrate LED Module, Color Temperature 3000K, 3500K, 4000K, 5000K


GU24 CFL Bulb Type: More Color Temperature Option 2700K, 4000K

Certification

UL/cUL, ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish/Shade	Dimension (H x W X E)	Energy Star
3-4310D-05-xxxxK	120V	15W	3000K / >80	990	Black / PC	14.1" x 10.0" x 5.7"	Yes
3-4310D-08-xxxxK	120V	15W	3000K / >80	990	Gray / PC	14.1" x 10.0" x 5.7"	Yes
3-4310D-05 (JA8)	120V	15W	3000K / >80	925	Black / PC	14.1" x 10.0" x 5.7"	---
3-4310D-08 (JA8)	120V	15W	3000K / >80	925	Gray / PC	14.1" x 10.0" x 5.7"	---

GU24 CFL Type

Model	Input Voltage	Finish	Lamp	Finish/Shade	Dimension (H x W X E)	Energy Star
3-4310-05	120V	Black	2 x 13W GU24	Black / PC	14.1" x 10.0" x 5.7"	---