

**Application**

Recessed wall luminaire with asymmetric light distribution that is ideal for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

**Materials**

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection  
 Composite installation housing  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 2.1 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -30° C  
 LED module wattage 8.4 W  
 System wattage 11.0 W  
 Controllability 0-10V, TRIAC, and ELV dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 480 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

**Available options**

- AMB Amber LED
- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- NTB Natural bronze (premium finish)
- RAL RAL finish

**Included (available for pre-shipment)**

- BB24065 Installation housing



**Recessed wall luminaire · Directed light**

	LED	A	B	C
<b>B33055</b>	8.4 W	12 1/2	2 3/4	5

