

GE
Lighting

LED Power Supply

Outdoor Dimming Driver (GE040/1050/MV-GL)
12164



imagination at work

Outdoor Dimming Driver

GE040/1050/MV-GL


Description: 40W 0.53/0.7/1.05A Dimmable Class 1 PSU

Input Voltage: 120-277V

Input Frequency: 50-60Hz



Max Output Power (W)	Output Current (A)	Output Voltage (V)	Efficiency Full Load @120V	Max Input Current (A)	Max THD @75W Output	Min PF 75W Output	Max Inrush Current (A/mS)	Surge Protection (kV/kA)	Isolated Dimming			Weight (lbs/kg)	IP Rating
									Protocol	Current Source	Dimming Range		
40	0.525 ± 5%	40-80	>86%	0.42 @ 120V 0.18 @ 277V	20%	0.9	See Page 6	6/3	0-10V	0.5mA	100%-10%	2.2/1	IP66
	0.700 ± 5%	30-60	>85%		20%	0.9		6/3	0-10V	0.5mA	100%-10%	2.2/1	IP66
	1.05 ± 5%	20-40	>84%		20%	0.9		6/3	0-10V	0.5mA	100%-10%	2.2/1	IP66



Product Features

Physical

- Unit must be installed within an electrical enclosure.
- Enclosure wiring must be rated to 600V & 105°C or higher.

Performance

- Classified as Class 1 as per UL8750.
- Dimming circuit is classified as Class 2 as stipulated in UL1310.
- Minimum ambient operating temperature: -40°C.
- Maximum allowable case temperature: 80°C.
- For reliability and failure rate information, contact GE Technical Sales Representative.
- Output current reduces if the case temperature exceeds 85°C.
- UL listed for operation in dry/damp locations (Outdoor Type 1).
- Tolerates of extended open circuit and short circuit conditions.
- Compliant to FCC Title 47 Part 15 Class A
- Surge resistance per IEEE/ANSI C136.2-2015 Location C-Low (6kV/3kA)
- Ground Leakage current of ≤ 0.4 mA


UL Conditions of Acceptability – E3430135

- The unit has been examined to comply with Class 1 Output Criteria
- The unit is only to be used in dry or damp locations
- The metal casing must be connected to EARTH.
- TVSS-GND (Yellow wire) shall be connected to fixture ground after hi-pot test using closest tab screw. THIS IS NOT A SAFETY GROUND!


Technical Information

GE040/1050/MV-GL


Lifetime (kHrs) vs Case Temperature (°C)




I_{out} v.s. V_{dim}



Efficiency vs Output Voltage @ 120V 60Hz




Efficiency vs Output Voltage @ 277V 60Hz




Technical Information

GE040/1050/MV-GL


PF vs Output Voltage @ 120V 60Hz




PF vs Output Voltage @ 277V 60Hz



THD vs Output Voltage @ 120V 60Hz



THD vs Output Voltage @ 277V 60Hz



Input Inrush Current


Input Voltage [Vrms]	Peak Current Pulse [Apk]	Pulse Duration (50% of Peak) [ms]
120	33	0.112
277	56.1	0.118

Input Ground Leakage Current


Input Voltage [Vrms]	Leakage Current [mA]
120	0.075
240	0.145

Product Dimensions

GE040/1050/MV-GL



Product Label



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2015 GE.

OLP3061 (Rev 09/15/15)