

LINE NO.	LAMP NUMBER	PRIMARY APPLICATION	DESIGN VOLTS	DESIGN WATTS	DESIGN AMPS	APPROX. INITIAL MAX CANDLE-POWER	BEAM SPREAD HOR. x VER. DEGREES	RATED AVERAGE LAB LIFE HOURS	BASE TYPE	MAXIMUM OVERALL LENGTH		FILAMENT TYPE
										in.	mm.	
PAR-46 Bulb 5¾" (146mm) Diameter (Continued)												
1	4633A*	Signal, School Bus, Amber	12.80	75.00	5.86	1,200	80 x 15	70④	MP	3.750	95	2 C-6
2	4633*	Signal, School Bus	12.80	75.00	5.86	6,000	80 x 15	70④	MP	3.750	95	C-6
3	4478	Flood, CIM	13.00	60.00	4.62	1,600	55 x 30	800④	2 Lug⑦	4.000	102	2 C-6⑧
4	4480	Headlamp, CIM	13.00	60.00	4.62	6,000	40 x 7	800④	2 Lug⑦	4.000	102	2 C-6⑧
5	4421⑥	Special Service	13.00	100.00	7.69	23,000	50 x 6	125④	MP	3.750	95	C-6
6	4007	Flood, Spot	Hi 13.00 Lo 13.00	100.00	7.69	50,000 20,000	5 x 6 7 x 13	25 25	MP	3.125	80	C-6 C-6
7	4537	Landing, Aircraft, W/Shield	13.00	100.00	7.69	200,000	11 x 6	11④	Screw	3.125	80	C-6
8	4537-2	Landing, Aircraft, W/Shield	13.00	100.00	7.69	200,000	11 x 6	11④	Slip-On	3.500	90	C-6
9	4537-3*	Landing, Aircraft, W/O Shield	13.00	100.00	7.69	200,000	11 x 6	11④	MP	3.125	80	C-6
10	4537-4	Landing, Aircraft, W/O Shield	13.00	100.00	7.69	200,000	11 x 6	11④	Screw	3.125	80	C-6
11	4537-5*	Landing, Aircraft, W/Shield	13.00	100.00	7.69	200,000	11 x 6	11④	MP	3.125	80	C-6
12	4049	Spot	13.00	150.00	11.54	300,000	15 x 7	15	MP	3.750	95	C-6
13	4049S	Spot, W/Shield	13.00	150.00	11.54	300,000	15 x 7	15	MP	3.750	95	C-6
14	4636	Signal	14.00	80.00	5.71	90,000	9 x 7	200④	MP	3.750	95	2 C-6⑨
15	4490A	Fog, Amber	28.00	50.00	1.79	9,000	40 x 5	400	Screw	3.750	95	CC-6
16	4578	Flood, CIM	28.00	60.00	2.14	1,600	55 x 30	800	2 Lug⑦	4.000	102	2 C-6⑧
17	H4578	Flood, CIM, Halogen	28.00	60.00	2.14	1,800	50 x 20	800	2 Lug⑦	4.000	102	2 C-6⑧
18	4880	Headlamp, CIM	28.00	60.00	2.14	6,000	40 x 7	800	2 Lug⑦	4.000	102	2 C-6⑧
19	H4880	Headlamp, CIM, Halogen	28.00	60.00	2.14	7,000	40 x 7	800	2 Lug⑦	4.000	102	2 C-6⑧
20	4579R	CIM, Red	Hi 28.00 Lo 28.00	80.00	2.86	3,600 1,600	25 x 7 25 x 7	400 400	3 Lug⑦	4.000	102	CC-6 CC-6
21	4579	Headlamp, CIM	Hi 28.00 Lo 28.00	80.00	2.86	24,000 11,000	25 x 7 25 x 7	400 400	3 Lug⑦	4.000	102	CC-6 CC-6
22	4813	Headlamp, CIM	28.00	90.00	3.21	10,000	50 x 10	800	2 Lug⑦	4.000	102	2 C-6⑧
23	H4813	Headlamp, CIM, Halogen	28.00	90.00	3.21	12,000	50 x 10	800	2 Lug⑦	4.000	102	2 C-6⑧
24	4814	Hi-Speed Driving, CIM	28.00	90.00	3.21	27,000	8 x 4	800	2 Lug⑦	4.000	102	2 C-6⑧
25	H4814	Hi-Speed Driving, CIM, Halogen	28.00	90.00	3.21	33,000	8 x 4	800	2 Lug⑦	4.000	102	2 C-6⑧
26	4572	Flood, Military	28.00	150.00	5.36	4,500	50 x 20	300	Screw	3.750	95	CC-6
27	4571	Flood, Military	28.00	150.00	5.36	7,000	80 x 20	300	Screw	3.750	95	CC-6
28	4570	Taxiing, Aircraft	28.00	150.00	5.36	32,000	50 x 9	300	Screw	3.750	95	CC-6
29	4551	Taxiing, Aircraft	28.00	250.00	8.93	75,000	50 x 10	25	Screw	3.750	95	CC-6
30	4553	Landing, Aircraft	28.00	250.00	8.93	300,000	11 x 12	25	Screw	3.125	80	CC-8
PAR-56 Bulb 7" (178mm) Diameter												
31	6006	Headlamp, Automotive, Hi Type 2D1, High/Low Beam	6.10 Lo 6.20	50.00 40.00	8.20 6.45	27,000 20,000	34 x 7 34 x 7	75 150	3 Lug⑦	5.000	127	C-6 C-6
32	4545	Spot, Marine Search [®]	12.00	100.00	8.33	220,000	9 x 5	100	Screw	4.500	114	C-6
33	4310	Swimming Pool	12.00	150.00	12.50	6,000	50 x 25	125④	Screw	4.500	114	C-6
34	4319	Swimming Pool	12.00	300.00	25.00	12,000	50 x 25	125④	Screw	4.500	114	2 C-6⑧

9

④ At 14 Volts ⑥ Alternate Terminal Available ⑦ Contact Type ⑧ In Series ⑨ In Parallel ⑩ Shielded
NOTE: CIM = Construction Industrial Machinery D.C. = Double Contact MP = Multipurpose Rt. = Right S.C. = Single Contact
**This part number is included for reference only and inventory may not be available.*