



A15

A19

K19

R14 Inter

GENERAL PURPOSE LAMPS

	Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life(hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
40	A15	Med	10023	●	40A15/CL/DL/FAN/BL/2/24	120	24	Clear Double Life Ceiling Fan Light	C, C-9	2000	350	2.38	3.50	
			10046	●	40A15/CL/DL/FAN	120	24	Clear Double Life Fan Light	C, C-9	2000	350	2.38	3.50	
			10034	●	40A15/CL/DL/FAN/2/12/BL	120	12	Clear Double Life Fan Light	C, C-9	2000	350	2.38	3.50	
			10133	●	40A15/CL/DL/BL	120	12	Clear Double Life Appliance	C, C-9	2000	350	2.38	3.50	
			10082	●	40A15/SL	120	120	Safeline Appliance	C, C-9	1000	420	2.38	3.50	
			11111	●	40A15/SW/FAN/BL/2/24	120	24	Soft White Ceiling Fan Light	C, C-9	1000	405	2.38	3.50	
			11533	●	40A15/SW/FAN/2/12/BL	120	12	Soft White Ceiling Fan	C, C-9	1000	405	2.38	3.50	
			10042	●	40A15/CL/FAN	120	24	Clear Ceiling Fan Light	C, C-9	1000	430	2.38	3.50	
			10022	●	40A15/CL/FAN/BL/2/24	120	24	Clear Ceiling Fan Light	C, C-9	1000	430	2.38	3.50	
			10036	●	40A15/CL/FAN/2/12/BL	120	12	Clear Ceiling Fan Light	C, C-9	1000	420	2.38	3.50	
			10141	●	40A15/2PK/RP	120	24	Clear Appliance	C, C-9	1000	430	2.38	3.50	
			10169	●	40A15/CL/BL/2/24	120	24	Clear Appliance	C, C-9	1000	430	2.38	3.50	
			10066	●	40A15/CL/APPL/2/12/BL	120	12	Clear Appliance	C, C-9	1000	420	2.38	3.50	
			10129	●	40A15/CL/BL	120	12	Clear Appliance	C, C-9	1000	430	2.38	3.50	
			10119	●	40A15	120	120	Inside Frost Appliance	C, C-9	1000	420	2.38	3.50	
			10117	●	40A15/IF/BL	120	12	Inside Frost Appliance	C, C-9	1000	420	2.38	3.50	
			Med Brass	10365		40A15/1	250	120	Inside Frost Appliance	B, C-9	1000	330	2.50	3.50
				10370		40A15/NEO	250	120	Neodymium Doped Appliance Lamp	B, C-9	1000	320	2.50	3.50
A19	Med	10897	●☀	40A/DAY/4/160/RP	120	160	Daylight	C, CC-8	1500	350	3.13	4.44		
		10864	●☀	40A/DAY/RP/4/48	120	48	Daylight	C, CC-8	1500	350	3.13	4.44		
		11100	●☀	40A/DAY/RP/2/24	120	24	Daylight	C, CC-8	1500	350	3.13	4.44		
		10829	●☀ ^{99,136}	40A/DAY/RP/4/48 @ 120 _volts, approximate 33 watts, 270 lumens, 3750 hours.	130	48	Daylight	C, CC-8	1500	350	3.13	4.44		
		10939	●☀	40A/DL/SW/4PK/RP	120	48	Soft White Double Life	C, CC-8	3000	390	3.13	4.44		
		11645	●☀	40A/DL/SW/2PK/RP	120	24	Soft White Double Life	C, CC-8	3000	390	3.13	4.44		
		11646	●☀	40AC/DL/2PK/RP	120	24	Clear Double Life	C, CC-8	3000	385	3.13	4.44		
		10996	●☀	40A/W/4/RP	120	48	Soft White	C, CC-8	1500	465	3.13	4.44		
		10977	●☀	40A/W/RP	120	24	Soft White	C, CC-8	1500	465	3.13	4.44		
		11223	●☀	40A/CL/RP	120	24	Clear	C, CC-8	1500	480	3.13	4.44		
		11036	●☀ ^{136,153}	40A/CL @ 120 _volts, approximate 35 watts, 350 lumens, 3750 hours	130	120	Clear	C, CC-8	1500	460	3.13	4.44		
		11060	●☀	40A/4/RP	120	48	Standard Frost	C, CC-8	1500	470	3.13	4.44		
		11010	●☀	40A/RP	120	24	Standard Frost	C, CC-8	1500	470	3.13	4.44		
		11059	●☀ ^{136,153}	40A @ 120 _volts, approximate 35 watts, 350 lumens, 3750 hours	130	48	Standard Frost	C, CC-8	1500	460	3.13	4.44		
		11011	●☀ ^{136,153}	40A/CVP @ 120 _volts, approximate 35 watts, 350 lumens, 3750 hours	130	24	Standard Frost	C, CC-8	1500	460	3.13	4.44		
K19	Med	10471	●	40K19/DR	120	24	Inside Frost Directional Reflector	C, CC-6	1150	385		4.13		
R14	Intermediate	14820	●	40R14N/RP	120	6	Reflector Mini Flood	C, CC-2V	1500			2.56		