



S28713

45W/LED/HID/5000K/277-347V/EX39
 45 watt - LED HID Replacement; 5000K; Mogul extended base;
 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9



S28713

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-935](#)

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent		
S28713	Hi-Pro	045923287138	277-347	45	300W	65W	175W		
Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	
Mogul Extended	EX39	45W/LED/HID/5000K/277-347V/EX39		Non-Dimmable	White	10-3/4"	3.69"	6000	
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack	Package Type	

50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	12	Box
DLC ID:		RoHS Compliant	UL Classification	Warranty	Thermal Management		
PL8JW0VCW1D1; PLFWZJA3QGO4 DLC Search		Yes	cULus - Wet Location Rated	5 Year Limited	More Details About		