



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21268 - 4 Watt B11 LED Filament; Clear; Candelabra base; 90 CRI; 5000K; 120 Volt



GENERAL

Company	SATCO
EA Height	4.13
EA Width	1.65
EA Length	1.65
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable; 120V only
Lamp Filament	LED Filament
Material	Glass / Nickel Plated Aluminum
Fixture Type	Candle
Status	Active
Style	Transitional
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.043A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Power Factor	0.75
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	15000
Beam Angle (degree)	300
Color Temp	Natural Light
CRI	90+
Dimming Type	Forward Phase or Reverse Phase or Phase Selectable
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	350L
Volts	120v
Watts	4W

PHYSICAL

Lamp Base	Candelabra
Finish	Clear
Housing Color	None
ANSI Base	E12
Lamp Type	B11
MOD Lamps	1.38
MOL	3.97

ADDITIONAL INFO

Warranty	2-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923205835
Case Cube	0.2259
Case Height	5.16
Case Length	10.39
Case Quantity	24
Case UPC	10045923205832
Case Weight	2.37
Case Width	7.28
EA Cube	0.0065
EA Height	4.13
EA Length	1.65
EA Quantity	1
EA Weight	0.07
EA Width	1.65
Inner Cube	0.0454
Inner Height	4.72
Inner Length	4.96
Inner Quantity	6
Inner UPC	20045923205839
Inner Weight	0.47
Inner Width	3.35
Pack Type	Box
Web Length	3.97
Web Width	1.38

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
UL Application	Filament LED Lamp
DLC Approved	No
Title 20	Yes
T24 Compliant	No