

Project Name

Location

Prepared By



SATCO S11904

4W/LED/T5/830/BP

Notes

General

Status	Active
Watts	4
Fluorescent Equivalent	8
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	12
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	400
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	No ballast or external driver required
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical

MOL	11.91
MOD	0.63
Weight (lb.)	0.08

Additional Information

Additional Info	Replaces F8T5/WW lamps
Shatter-Proof Type	PET Coated
Installation Notes	Direct wire 120-277V line voltage; Double ended wiring
Warranty	5 Year Limited - T5 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved

