



# S11906

4W/LED/T5/865/BP

4W T5 LED; Miniature bi-pin base; 6500K; 50000 Average rated hours; 400 Lumens; 120-277V; Type B; Ballast Bypass; Double Ended Wiring



## Features

- No ballast or external driver required
- Available in 6", 9", 12", & 21"
- Direct wire 120-277V line voltage
- Double ended wiring
- NSF Approved
- PET Shatterproof coated
- 5 year Limited warranty

S11906

Replaces F8T5/D lamps

| Item Number | UPC          | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Power Factor | Lamp Shape |
|-------------|--------------|---------|-------|---------------------|------------------------|--------------|------------|
| S11906      | 045923119064 | 120-277 | 4     | 50/60Hz             | 8W                     | 0.90         | T5         |

| Base             | ANSI Base | Lamp Code        | Dimmable/Non-Dimmable | Finish  | MOL In Inches | MOD In Inches | Initial Lumens |
|------------------|-----------|------------------|-----------------------|---------|---------------|---------------|----------------|
| Miniature Bi-Pin | G5        | 4W/LED/T5/865/BP | Non-Dimmable          | Frosted | 11-29/32"     | 0-5/8"        | 400            |

| Average Rated Hours | Kelvin Temp | Color    | CRI | Beam Spread Deg | Operating Temperature                    | Pack | CEC Status                    |
|---------------------|-------------|----------|-----|-----------------|------------------------------------------|------|-------------------------------|
| 50000               | 6500        | Daylight | 80  | 240             | -25C (-13F) to a maximum of +45C (+113F) | 10   | Lawful for sale in California |

| Material | RoHS Compliant | UL or ETL Listed | UL Classification                      | Warranty                       |
|----------|----------------|------------------|----------------------------------------|--------------------------------|
| Glass    | Yes            | Yes              | cULus Classified - Damp Location Rated | <a href="#">5 Year Limited</a> |



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051