## PL H 5.5W DIR TITANIUM LED SERIES











- Easy to install Plug & Play Direct
- Ballast output power control technology
- Exceptional efficacy 102 LPW
- Dimmable on 0-10V circuits
- Compatible with most electronic ballasts
- Available in 2700K, 3000K, 3500K & 4000K CCT



























### PL PRODUCT FEATURES

High Performance - Ballast Smart Control

The PL DIR lamp's ballast smart control technology allows for high performance even on lower powered ballasts, making it a suitable replacement for 13W and 18W CFL PL lamps.

Ballast Type	Lumens	Bare Lamp
13W	550	5W
18W	560	5.5W

#### Adjustable Base










This PL H lamp features a base that can be rotated 310° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

# PL H 5.5W DIR TITANIUM LED SERIES










1.34"(34mm)

G24q & GX24q (4-pin CFL) Base: Voltage: **Ballast compatible 120-277V** 

**Dimmable:** PF: 0.9

Lifetime (L70): 50,000 hrs Weight: 0.15lb / 68g



### **SPECIFICATIONS**

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
5.5PLH/827/DIR/R	57895	5.5	Soft White 2700K	82	520	95	110°
5.5PLH/830/DIR/R	57896	5.5	Warm White 3000K	82	550	100	110°
5.5PLH/835/DIR/R	57897	5.5	Neutral White 3500K	82	550	100	110°
5.5PLH/840/DIR/R	57898	5.5	Cool White 4000K	82	560	102	110°

### **BALLAST PERFORMANCE**

Ballast Type	Bare Lamp (W)	System (W)	2700K Lumens	3000K Lumens	3500K Lumens	4000K Lumens
13W	5	6.7	480	500	500	550
18W	5.5	7.5	520	550	550	560

Testing Method: Power and lumen output will vary based on number of lamps, ballast and fixture type. Above data is indicative only.

<sup>\*</sup> Suitable for damp locations. Not for use where directly exposed to weather or water \*\* Not intended for use in enclosed fixtures

<sup>\*\*\*</sup> Full installation guide and more details available on website