Presented By: **Candela Corporation** Contact Phone: (800) 922-9226

Contact E-mail:

sales@candelacorp.com



GE Lighting


97482 - 50/250/1-1PK

GE Soft White A21


• Use original GE's Soft White when you need a light without glare and harsh shadows.

- Specifically designed for 3-way lamps in your home or office, GE 3-way bulbs offer a range of light levels. Choose
- the low light setting for energy savings, higher settings for general and activity lighting.

. Choose the low light setting for energy savings, higher settings for general and activity lighting.









GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament **Bulb Finish** Wattage Voltage Rated Life **Bulb Material Primary Application**

Customer Name:

Project Name: Fixture Type:

> Incandescent - A-line A21 Medium Screw (E26) CC-8/CC-25 Soft white 50/200/250 120 1200 hrs Soft glass 3-Way

PHOTOMETRIC CHARACTERISTICS

620 /3335 /3955 Initial Lumens 12 /15 /16 Nominal Initial Lumens per Watt

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) Light Center Length (LCL)

5.2500 in(133.4 mm) 2.625 in(66.7 mm) 2.625 in(66.7 mm) 3.870 in(98.3 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168905015



CAUTIONS & WARNINGS

Warning

- Risk of Fire
- Use in fixture rated for this product.