




# AdaptaBeacon® Adverse Location 105 Series


Cat. No's.  
105SLED  
105FLED  
105SINH  
105FINH  
105ST




Cat. No's.  
105HIST  
105DHIST



Cat. No. 105BM Mounting Bracket  
(use with 105BX)



Cat. No. 105BX  
Outlet Box Attachment



Cat. No. 105PM  
Pipe Mount Attachment

Cat. No.	Module Type	Lamp Ratings	Peak Candlepower	Voltage	Current	Replacement Lamp
105SLED*-G1	Steady-On LED	120,000 hours <sup>1,2</sup>	Color Dependent	24V DC	0.062A	—
105SLED*-N5	Steady-On LED	120,000 hours <sup>1,2</sup>	Color Dependent	120V AC	0.022A	—
105FLED*-G1	Flashing LED	100,000 hours <sup>1,2</sup>	Color Dependent	24V DC	0.062A	—
105FLED*-N5	Flashing LED	100,000 hours <sup>1,2</sup>	Color Dependent	120V AC	0.022A	—
105SINH**-G1	Steady-On Halogen	20W, 20,000 hours <sup>1,2</sup>	2839	24V DC	0.8A	50LMP-20WH or Ind. Trade No. 1692 (Incandescent)
105SINH**-G5	Steady-On Halogen	20W, 20,000 hours <sup>1,2</sup>	2839	24V AC	0.8A	50LMP-20WH or Ind. Trade No. 1692 (Incandescent)
105SINH**-N5	Steady-On Halogen	25W, 20,000 hours <sup>1,2</sup>	2198	120V AC	0.2A	50LMP-25WH or Ind. Trade No. 25T8DC (Incandescent)
105FINH**-G1	Flashing Halogen	20W, 20,000 hours <sup>1,2</sup>	2839	24V DC	0.8A	50LMP-20WH or Ind. Trade No. 1692 (Incandescent)
105FINH**-G5	Flashing Halogen	20W, 20,000 hours <sup>1,2</sup>	2839	24V AC	0.8A	50LMP-20WH or Ind. Trade No. 1692 (Incandescent)
105FINH**-N5	Flashing Halogen	25W, 20,000 hours <sup>1,2</sup>	2198	120V AC	0.2A	50LMP-25WH or Ind. Trade No. 25T8DC (Incandescent)
105ST**-G1	3 Joule Strobe	3,000 hours <sup>3</sup>	300,000	24V DC	0.3A	91B-ST
105ST**-N5	3 Joule Strobe	3,000 hours <sup>3</sup>	300,000	120V AC	0.1A	92-ST
105ST**-R5	3 Joule Strobe	3,000 hours <sup>3</sup>	300,000	240V AC	0.02A	92-ST
105DHISTC-FJ	Fire Alarm (UL 1971) 8 Joule Strobe	3,000 hours <sup>3</sup>	26 cd wall (dome out) 24 cd wall (dome down) 26 cd ceiling	20-30V DC	1.08 - 0.83 A	92-ST
105DHIST***-FJ	High Intensity 8 Joule Strobe	3,000 hours <sup>3</sup>	800,000	20-30V DC	1.08 - 0.83 A	92-ST
105HIST**-N5	High Intensity 8 Joule Strobe	3,000 hours <sup>3</sup>	800,000	120V AC	0.1A	92-ST
105HIST**-R5	High Intensity 8 Joule Strobe	3,000 hours <sup>3</sup>	800,000	240V AC	0.05A	92-ST
105HIST**-EK	High Intensity 8 Joule Strobe	3,000 hours <sup>3</sup>	800,000	12-48V DC	0.05A	92-ST

\*Lens and light source (LED) color: A - amber, B - blue, G - green, R - red.  
\*\*Lens color: A - amber, B - blue, C - clear, G - green, M - magenta, R - red.  
\*\*\*Lens color: A - amber, B - blue, G - green, M - magenta, R - red

<sup>1</sup>At nominal operating voltage.

<sup>2</sup>Projected lamp life based on manufacturer's calculated lamp life @ 65 fpm and 50% duty cycle.

<sup>3</sup>Strobe tube life @ operating power to 75% efficiency.