

RAIL LED I Bath Vanity

52100 / 52102 / 52103 / 52104

- ETL, cETL IP65
- Suitable for damp locations
- CRI 90+
- Dimmable with Triac Dimmer
- Energy Star
- Title 24 JA8 Compliant

Job Name : _____

Job Type : _____


Quantity : _____

Comments : _____



PRODUCT DESCRIPTION

Tubular shaped White acrylic diffusers mount to frames of Polished Chrome, Satin Nickel, or Black. Powered by 3000K LED these fixtures work well in a variety of contract applications.



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT
52100	18"L x 4.75"H x 2.50"EXT	0.70 LB
52102	24"L x 4.75"H x 2.50"EXT	0.85 LB
52103	30"L x 4.75"H x 2.50"EXT	1.10 LB
52104	36"L x 4.75"H x 2.50"EXT	1.30 LB

LAMPING

MODEL	BULB TYPE	CRI	LUMENS RATED	DEL	COL TEMP.	DIMMABLE	INPUT
52100	(1) 12W LED (Integrated)	90+	1140	930	3000K	Triac Dimmer	120V
52102	(1) 16W LED (Integrated)	90+	1520	1400	3000K	Triac Dimmer	120V
52103	(1) 20W LED (Integrated)	90+	1900	1690	3000K	Triac Dimmer	120V
52104	(1) 24W LED (Integrated)	90+	2280	2040	3000K	Triac Dimmer	120V

FINISHES OPTIONS:

- Satin Nickel (SN)
- Polished Chrome (PC)
- Black (BK)



MATERIAL:
Aluminum + Acrylic

RATINGS:
ETL cETL IP65
Damp Location
Energy Star
Title 24 JA8 Compliant
ADA
Dimmable



ADDITIONAL:
RATED LIFE : 50,000 hours
INSTALL UP/DOWN: Both
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product