S28714

54W/LED/HID/5000K/277-347V/EX39
54 watt - LED HID Replacement; 5000K; Mogul extended base; 277-347 volts

S28714

Features
- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications
- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector 80-935

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S28714	Hi-Pro	045923287145	277-347	54	300W	85W	250W

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	54W/LED/HID/5000K/277-347V/EX39	Non-Dimmable	White	10-3/4"	3.69"	7200

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type

50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	12	Box

DLC ID:	RoHS Compliant	UL Classification	Warranty	Thermal Management
PLF6RDNNBILQ; PLMML5AKJRFU DLC Search	Yes	cULus - Wet Location Rated	5 Year Limited	More Details About