G9 Dimmable LED Lamp

Item Number 51641

Specifications

•	
Energy Used (Watts)	5
Incandescent Equivalent Wattage	40
Domestic Code	5G9/LED/DIM/CL/30
Volts	120
Brightness (Lumens)	500
Average Rated Hours	25,000
Life (in years)*	22.8
Light Appearance (Kelvin)	3000
Beam Spread	330°
CRI	80
Efficacy (LPW)	100
Estimated Yearly Energy Cost**	\$0.60
Package Type	Box
Can be used in totally enclosed fixtures.	



Physical Characteristics

_	
Color Designation	Warm White
Finish	Clear
Housing Material	Ceramic
Base	G9
MOL	2.13"











Limited Warranty

This lamp is warranted to be free from defects in material and workmanship for 5 years (based on using 3 hours per day).

Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock Do not use where exposed to water or weather.
- Suitable for Damp Locations The lamp is suitable for use in wet locations when used in an outdoor rated fixture.
- Do not open no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

^{*}Based on 3 hrs./day

^{**} Based on 3 hrs./day 11¢/kWh - Cost depends on rates and use.

G9 LED Dimmer Compatibility

Brand	Model
Lutron	DVCL-153P, DVCL-153PR-WH, PD-6WCL, MACL-153M, MRF2-6CL, DVCL-253P-WH, CTCL-153P, SCL-153P, TGCL-153PH-WH, TTCL-100, PD-10NXD

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.