



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8604 - 6.5 Watt; LED MR16; 3000K; 40 deg. Beam Angle; GU10 base; 120 Volt; Carded



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	120V
Lumens:	500L
CRI:	80+
R9 Value :	14
CCT (Kelvins):	3000K - Soft White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Forward Phase (TRIAC) or Reverse Phase or Phase Selectable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Phase Cut (TRIAC); 120V only
Incandescent Equivalent :	50W
Operating Temperature :	-13F to +113F (-25C to +45C)
Candlepower :	700
Spot Type :	FL - Flood
Power Factor :	0.92
Light Source:	LED
CBCP :	700
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923086045
Each Quantity:	1
Each Dimensions:	2.09 x 4.50 x 7.00

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Bi Pin GU10
Shape:	MR16
Finish:	White
Lens Finish:	Array White
Dimensions (In.):	MOL: 2.165 - MOD: 1.969
Weight (Lbs.):	0.08
Material:	Plastic
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S8604 - 6.5 Watt; LED MR16; 3000K; 40 deg. Beam Angle; GU10 base; 120 Volt; Carded

DIMMER COMPATIBILITY

Lutron	CTRP-253P
Lutron	DVLV-600P
Lutron	MA-PRO
Lutron	NTRP-250
Legrand	RH703PTUTC
Lutron	SLV-600P