



## Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

## Areas of application

- Airfield Lighting

## Product datasheet

### Technical data

#### General product information

Application	Airfield/Airport
Product Remark	– s (Operating Position) = Vertical, base down – p (Operating Position) = Horizontal

#### Electrical data

Current (A)	6.6 A
Type of Current	AC

#### Light technical data

Light Center Length - LCL (in)	1 in
Light Center Length - LCL (mm)	25.4 mm

#### Physical attributes

Maximum Overall Length (in)	1.752 in
Maximum Overall Length (mm)	44.5 mm
Diameter d (in)	0.453 in
Diameter d (mm)	11.50 mm
Filament	C-8
Filament Dimensions Length (in)	0.1300 in
Filament Dimensions Length (mm)	3.3 mm
Filament Dimensions Width (in)	0.055 in
Filament Dimensions Width (mm)	1.4 mm

#### Additional product data

Operating Position	s 90
Class	C (gas)

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	4008321100122	Folding box (SKU)	1	4.4 in x 1.7 in x 1.7 in	
	4008321100139	Shipping box (Case)	12	7.1 in x 5 in x 5.5 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.