


INCANDESCENT LAMPS

General Service



Bulb	Base	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Volts	Lumens	Avg. Life	Design Filament	MOL	Beam Spread
50/100/150 WATT												
A21	Med.	8010	1	A21SW3W150	Soft White 3-Way 50/100/150	12/60	130	560/1200/1760	2500	CC-8	5.25"	-
		101240	X,N,1	A21FR50/150/ND	Frost 3-Way 50/100/150 Neodymium PureLite®	12/60	120	380/1000/1380	5000	CC-8	5.25"	-
53 WATT												
A19	Med.	76007	Ⓔ \$	A19CL53/H	Clear	12/120	120	1050	1000	CC-8	4.25"	-
		76002	Ⓔ \$	A19SW53/H	Soft White	12/120	120	1050	1000	CC-8	4.25"	-
PAR30	Med.	70310	Ⓔ †,17	HP30FL53/XIR	Flood XIR®	1/15	120	1050	3500	CC-8	3.62"	30°
PAR30L	Med.	70311	Ⓔ †,17	HP30FL53L/XIR	Flood XIR®	1/15	120	930	3500	CC-8	4.75"	30°
PAR38	Med.	70312	Ⓔ †,17	HP38FL53/XIR	Flood XIR®	1/15	120	960	3500	CC-8	5.31"	25°
54 WATT												
A19	Med.	288584	\$	A19FR54/10	Frost Prism® Ultra Life®	20/120	130	450	10000	C-9M	4.25"	-
60 WATT												
A15	Cand.	10007		A15CL60/E12	Clear	20/120	120	530	2000	C-9	3.50"	-
		10008		A15WH60/E12	White	20/120	120	520	2000	C-9	3.50"	-
	Med.	6117		A15CL60	Clear	20/120	130	530	3000	C-9	3.50"	-
		126117		A15CL60/120	Clear	20/120	120	620	3000	C-9	3.50"	-
		101234	X, N	A15CL60/ND	Clear Neodymium PureLite®	10/50	120	530	5000	CC-9	3.50"	-
		6118		A15FR60	Frost	20/120	130	520	3000	C-9	3.50"	-
		6147		A15RS60/CS	CoverShield®	20/120	130	-	1500	C-9	3.50"	-
A19	Med.	103712	L, AI	A19CL60	Clear	120	130	620	1500	C-9	4.25"	-
		6225	L	A19CL60/120	Clear	120	120	590	1500	CC-6	4.25"	-
		6325	L	A19CL60/5	Clear	120	130	545	5000	C-9	4.25"	-
		103010	L	A19CL60/P10	Clear Prism® Ultra Life®	20/120	120	480	10000	C-9M	4.25"	-
		101242	N	A19CL60/ND	Clear Neodymium PureLite®	20/120	120	600	5000	CC-6	4.25"	-
		101180	3	A19CL60/SB	Clear Silver Bowl Prism®	12/120	130	-	2500	C-9	4.25"	-
		103704	L, AI	A19FR60	Frost	120	130	590	1500	C-9	4.25"	-
		6321	L	A19FR60/5	Frost	120	130	510	5000	C-9	4.25"	-
		103024	L	A19FR60/P10	Frost Prism® Ultra Life®	20/120	120	480	10000	C-9M	4.25"	-
		101194	N	A19FR60/ND	Frost Neodymium PureLite®	20/120	120	600	5000	CC-6	4.25"	-
		101184	3	A19FR60/SB	Inside Frost Silver Bowl Prism®	12/120	130	-	5000	C-9	4.25"	-
		6221	L	A19SW60/120	Soft White	120	120	530	1500	C-9	4.25"	-
		8011		A19BG60	Yellow Bug	20/120	130	-	2000	C-9	4.25"	-
		101196	X	A19GRO60	Plant Grow	12/120	120	480	2000	C-9	4.25"	-
		6352		A19RED60C	Ceramic Red	12/120	130	-	2000	C-9	4.25"	-

Ⓔ Means this lamp meets Federal Minimum Efficiency standards.
Incandescent lamp symbols, footnotes and abbreviations are located on pages 151-153.