Presented By: **Candela Corporation** Contact Phone: (800) 922-9226

Contact E-mail:

sales@candelacorp.com





GE Lighting

14016 - 65R40/FL/MI-6PK

GE Soft White BR40

- Use original GE's Soft White when you need a light without glare and harsh shadows.
- Replace ordinary light bulbs with GE Flood and Spotlight in all your track and recessed lighting fixtures.





CAUTIONS & WARNINGS

Warning

• Unexpected lamp rupture may cause injury, fire, or property damage

- Avoid direct water, liquid or metal contact.
- Risk of Fire
- Keep combustible materials away from lamp.
- Use in fixture rated for this product.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Wattage Voltage Rated Life **Bulb Material Primary Application** Incandescent - Reflector BR40 Medium Screw (E26) CC-6 65 120 2000 hrs Soft glass Indoor Floodlight

PHOTOMETRIC CHARACTERISTICS

| Initial Lumens | 730 |
|---------------------------------|-----|
| Nominal Initial Lumens per Watt | 11 |

DIMENSIONS

Maximum Overall Length 6.56 cm (MOL) Bulb Diameter (DIA) 5 cm Bulb Diameter (DIA) (MAX) 5 cm

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168140164