A19 / A21 LINE

- Suitable to replace 40W, 60W, 75W, 100W incandescent lamps
- High CRI and R values (R9 57, R13 95)
- Suitable for use in totally enclosed fixtures

SPECIFICATIONS

Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.	ES / JA8 / T20
36552	6A19DIM/927	2700K	480	92	90	Yes	40W	230°	25,000	120V	Yes	√ / N.A. / √
36553	6A19DIM/930	3000K	480	92	90	Yes	40W	230°	25,000	120V	Yes	√ / N.A. / √
98560	9A19DIM/930	3000K	800	92	89	Yes	60W	240°	25,000	120V	Yes	√ / N.A. / √
98561	9A19DIM/940	4000K	820	92	91	Yes	60W	240°	25,000	120V	Yes	√ / N.A. / √
36554	9A19DIM/927/R	2700K	800	92	89	Yes	60W	230°	25,000	120V	Yes	√ / N.A. / √
36555	9A19DIM/930/R	3000K	820	92	91	Yes	60W	230°	25,000	120V	Yes	√ / N.A. / √
36560	9A19DIM/935/R	3500K	840	92	93	Yes	60W	230°	25,000	120V	Yes	√ / N.A. / √
36556	9A19DIM/940/R	4000K	860	92	96	Yes	60W	230°	25,000	120V	Yes	√ / N.A. / √
36557	9A19DIM/950/R	5000K	860	92	96	Yes	60W	230°	25,000	120V	Yes	√ / N.A. / √
98565	9A19DIM/927/GU24/R	2700K	860	92	96	Yes	60W	240°	25,000	120V	Yes	√ / √ / √
36675	9A19DIM/927/GU24/RC	2700K	800	92	89	Yes	60W	230°	25,000	120V	Yes	- / N.A. / -
36676	9A19DIM/930/GU24/RC	3000K	820	92	91	Yes	60W	230°	25,000	120V	Yes	- / N.A. / -
36677	9A19DIM/940/GU24/RC	4000K	860	92	96	Yes	60W	230°	25,000	120V	Yes	- / N.A. / -
36678	9A19DIM/950/GU24/RC	5000K	860	92	96	Yes	60W	230°	25,000	120V	Yes	- / N.A. / -
98141	11A19DIM/927	2700K	1,100	92	100	Yes	75W	240°	25,000	120V	Yes	√ / N.A. / √
98142	11A19DIM/930	3000K	1,150	92	105	Yes	75W	240°	25,000	120V	Yes	√ / N.A. / √
98143	11A19DIM/940	4000K	1,200	92	109	Yes	75W	240°	25,000	120V	Yes	√ / N.A. / √
36679	11A19DIM/927/R	2700K	1,100	92	100	Yes	75W	230°	25,000	120V	Yes	- / N.A. / -
36680	11A19DIM/930/R	3000K	1,150	92	105	Yes	75W	230°	25,000	120V	Yes	- / N.A. / -
36681	11A19DIM/940/R	4000K	1,200	92	109	Yes	75W	230°	25,000	120V	Yes	- / N.A. / -
36682	11A19DIM/950/R	5000K	1,200	92	109	Yes	75W	230°	25,000	120V	Yes	- / N.A. / -
98147	15A21DIM/927/N	2700K	1,600	92	107	Yes	100W	240°	25,000	120V	Yes	√ / N.A. / √
98148	15A21DIM/930/N	3000K	1,650	92	110	Yes	100W	240°	25,000	120V	Yes	√ / N.A. / √
98149	15A21DIM/940/N	4000K	1,700	92	113	Yes	100W	240°	25,000	120V	Yes	√ / N.A. / √

A19 / A21 VALUE SELECT LINE

GREENCREATIVE

- Suitable to replace 60W, 75W, 100W incandescent lamps
- Provides comfortable, diffused light
- Dimmable with forward and reverse phase controls

SPECIFICATIONS

Product	Model	CCT	Lumens	CRI (typ.)	LPW	Dim	Equiv.	Beam Angle	Life (hrs)	Voltage	Encl.	ES
36548	9A19DIM/827/R	2700K	800	82	89	Yes	60W	230°	25,000	120V	Yes	√
36549	9A19DIM/830/R	3000K	820	82	91	Yes	60W	230°	25,000	120V	Yes	√
36559	9A19DIM/835/R	3500K	840	82	93	Yes	60W	230°	25,000	120V	Yes	√
36550	9A19DIM/840/R	4000K	860	82	96	Yes	60W	230°	25,000	120V	Yes	√
36551	9A19DIM/850/R	5000K	860	82	96	Yes	60W	230°	25,000	120V	Yes	√
97908	9A19DIM/827/GU24/R	2700K	800	82	89	Yes	60W	240°	25,000	120V	Yes	√
97909	9A19DIM/830/GU24/R	3000K	820	82	91	Yes	60W	240°	25,000	120V	Yes	√
97910	9A19DIM/840/GU24/R	4000K	860	82	96	Yes	60W	240°	25,000	120V	Yes	√
36544	9.5A19DIM/827	2700K	800	82	84	Yes	60W	230°	15,000	120V	Open	√
36545	9.5A19DIM/830	3000K	820	82	86	Yes	60W	230°	15,000	120V	Open	√
36546	9.5A19DIM/840	4000K	860	82	91	Yes	60W	230°	15,000	120V	Open	√
36547	9.5A19DIM/850	5000K	860	82	91	Yes	60W	230°	15,000	120V	Open	√
98138	11A19DIM/827	2700K	1,100	82	100	Yes	75W	240°	25,000	120V	Yes	√
98139	11A19DIM/830	3000K	1,150	82	105	Yes	75W	240°	25,000	120V	Yes	√
98140	11A19DIM/840	4000K	1,200	82	109	Yes	75W	240°	25,000	120V	Yes	√
36615	13A19DIM/827	2700K	1,100	82	85	Yes	60W	230°	15,000	120V	Yes	√
36616	13A19DIM/830	3000K	1,150	82	88	Yes	60W	230°	15,000	120V	Yes	√
36617	13A19DIM/840	4000K	1,200	82	92	Yes	60W	230°	15,000	120V	Yes	√
36618	13A19DIM/850	5000K	1,200	82	92	Yes	60W	230°	15,000	120V	Yes	√
98144	15A21DIM/827	2700K	1,600	82	107	Yes	100W	240°	25,000	120V	Yes	√
98145	15A21DIM/830	3000K	1,650	82	110	Yes	100W	240°	25,000	120V	Yes	√
98146	15A21DIM/840	4000K	1,700	82	113	Yes	100W	240°	25,000	120V	Yes	√
98150	15A21DIM/827/GU24	2700K	1,600	82	107	Yes	100W	240°	25,000	120V	Yes	√