



# S28715

80W/LED/HID/5000K/277-347V/EX39  
 80 watt - LED HID Replacement; 5000K; Mogul extended base;  
 277-347 volts

### Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

### Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9



S28715

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-935](#)

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent	
S28715	Hi-Pro	045923287152	277-347	80	400W	100W	320W	
Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	80W/LED/HID/5000K/277-347V/EX39		Non-Dimmable	White	9-1/4"	5.87"	10640

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	4	Box
DLC ID:		RoHS Compliant	UL Classification	Warranty	Thermal Management		
PL1XBF8N9DWC; PLTP63LREWFZ <a href="#">DLC Search</a>		Yes	cULus - Wet Location Rated	<a href="#">5 Year Limited</a>	<a href="#">More Details About</a>		