


901006351U


LED 6 DC 350mA Plastic

LED 6W DC 350mA - LED Driver, Constant Current, Plastic Housing. Potted, with Leads

Current: DC Availability: B







Specs

Field MTBF: 50000.0 h Power: 6.0 W

Input specs

Inrush current limiter: true Power factor: 0.5 0.07-0.12 A Input current: 50/60 Hz Input frequency: 120.0-277.0 V Input voltage: Efficiency: 70 %

Output specs

350.0 mA Output current: Output voltage range: 2.0-20.0 V Output current tolerance: 8.0 %

Dimmable

Dimmable: false

Protections

Over temperature protection: true Reinforced insulation: true Input voltage surge protection: true Secondary protection: false

Environment

Ta min: -25.0 °C IP· 67 Ta max: 50.0 °C Tc: 71.0 °C

IP67 certification:

Storage temp.: -10...70 °C

Standards

VDE EMC:

Class 2:

UL: E322460

VDE Safety: FCC Class: Class B Class II: true

Mechanical

Potted: Input wire size AWG: 18 0 AWG Case color: black 18.0 AWG Output wire size: Weight: 0.0945 kg Output wire color: blue/red 45.0 mm Casing width: Casing length: 45.0 mm Plastic Case material: Input wires color: black/white 25.0 mm Casing height: Input wire length: 200 mm Output wire length: 200 mm INPUT WIRE DOUBLE INSULATED (BOOLEAN): true

Marketing

Applications:

LED in- and outdoor lighting
 Architectural lighting
 Orientation lighting
 Ambience lighting
 Task, Table and Floor lighting

Features

Designed for IP67
 Reinforced insulation from input to output
 Small form factor
 Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal

5. AC Input
6. Fast Start-Up Time
7. 120-277V Input
8. High-efficiency, high Vout range (up to 2-20V)