GE
Lighting

GE Halogen PAR Lamps



Silver Coating Technology

Exclusive Thin Film HIR™ design

Widest variety of Energy and Long Life Options

Ideal for:

- Accent Lighting
- Merchandising Displays
- General Illumination in Office Lobbies, Public Buildings

GE Technology Advantage	IR Film	Aluminum Coating & IR Plus Film	Silver Coating & IR Plus Film
"GOOD"	"BETTER"	"BETTER"	"OPTIMUM"

Energy Savings

NEW **Standard**
Crisp, white light
Perfect CRI - 100
1500 Hours
38W, 60W & 90W

NEW **HIR™ Plus**
50W & 60W 2600 Hours
70W, 80W & 90W 3000 Hours

HIR™ Plus
Up to 54% more efficient
Up to 36% energy savings
Up to 110% longer life
4200 Hours

HIR™ Plus XL
Up to 37% more efficient
Up to 17% energy savings
Up to 420% longer life
8400 Hours

Standard & Plus
Crisp, white light
Perfect CRI – 100
2000 – 2500 Hours
90W at 2500 Hours

HIR™*
Up to 28% more efficient
Up to 22% energy savings
Up to 50% longer life
3000 Hours

HIR XL®*
Lasts 6000 Hours
Up To 10% energy savings

Long Life

• All comparison are made against Standard & Halogen Plus at same/similar lumen output

imagination at work

GE Halogen Product Offering

Standard	GE Product Code	Description	Life	Lumens	CBCP
NEW	69135	38PARH1500SP10	1500	520	6600
	69136	38PARH1500FL10	1500	520	2000
	62703	60PARH1500SP10TP	1500	1070	17400
	62704	60PARH1500FL25TP	1500	1070	4050
	62705	90PARH1500SP10TP	1500	1790	26450
	62706	90PARH1500FL25TP	1500	1790	6850

HIR™ Plus	GE Product Code	Description	Life	Lumens	CBCP
NEW	62713	50PARHIR+3KSP10T	2600	900	13700
	62714	50PARHIR+3KFL25T	2600	900	3400
	68979	70PARHIR+3KS10P1	3000	1305	19000
	68980	70PARHIR+3KS8P1	3000	1305	26000
	68978	70PARHIR+3KF25P1	3000	1305	4500
	66302	80PARHIR+3KS10P1	3000	1600	22700
	66303	80PARHIR+3KF25P1	3000	1600	5200
	62715	90PARHIR+3KSP10T	3000	1900	26500
	62716	90PARHIR+3KFL25T	3000	1900	6200
	90512	45PAR/HIR+/SP10	4200	870	14100
	90513	45PAR/HIR+/FL25	4200	870	3500
	90515	48PAR/HIR+/SP10	4200	970	15500
	90519	48PAR/HIR+/FL25	4200	970	3800
	71446	55PAR/HIR+/SP10	4200	1120	17500
	71598	55PAR/HIR+/FL25	4200	1120	4100
	69819	55PAR/HIR+/WFL	4200	1120	1200
	90520	60PAR/HIR+/SP10	4200	1260	19000
	90529	60PAR/HIR+/FL25	4200	1260	4700
	90601	67PAR/HIR+/SP10	4200	1500	22000
	90602	67PAR/HIR+/FL25	4200	1500	5000
	90605	83PAR/HIR+/SP10	4200	2030	30000
	90606	83PAR/HIR+/FL25	4200	2030	7000

HIR™ Plus XL	GE Product Code	Description	Life	Lumens	CBCP
	76142	53PARHIR+XL/SP10	7800	940	15000
	76143	53PARHIR+XL/FL25	7800	940	3700
	62232	75PARHIR+XL/8K/SP10T	8400	1500	22000
	62231	75PARHIR+XL/8K/FL25T	8400	1500	5000

For additional product and application information, please consult GE's Website: www.gelighting.com

© 2013 GE 68011 8/2013 Printed in USA

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

GE Halogen Product Offering

PAR20	GE Product Code	Description	Life	Lumens	CBCP
NEW	69163	38PAR20H/FL25	1500	490	1450
	69164	38PAR20H/SP10	1500	490	3800

PAR20 HIR™ Plus	GE Product Code	Description	Life	Lumens	CBCP
NEW	69148	38PAR20HIR+/FL30	3000	530	1300
	69149	38PAR20HIR+/SP15	3000	530	2600

PAR30 Short Neck	GE Product Code	Description	Life	Lumens	CBCP
NEW	69166	38PAR30H/FL25	1500	580	1750
	69167	38PAR30H/SP10	1500	580	5700

PAR30 Short Neck HIR™ Plus	GE Product Code	Description	Life	Lumens	CBCP
	76126	48PAR30HIR+/FL30	4200	840	2600
	76127	48PAR30HIR+/SP10	4200	840	10200
	66580	48PAR30HIR+/NFL	4200	840	2600

PAR30 Long Neck	GE Product Code	Description	Life	Lumens	CBCP
NEW	69168	38PAR30L/H/FL25	1500	550	1500
	69169	38PAR30L/H/SP10	1500	550	3800

PAR30 Long Neck HIR™ Plus	GE Product Code	Description	Life	Lumens	CBCP
	73546	48PAR30L/HIR+/FL	4200	850	2500
	74779	48PAR30L/HIR+/SP	4200	850	9500

For additional product and application information, please consult GE's Website: www.gelighting.com

© 2013 GE 68011 8/2013 Printed in USA

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.