



# Xitanium LED drivers outdoor Dimmable (US)

## Xitanium 0-10V 12-24V DIMMING CONTROLLER

Xitanium Constant Current Outdoor product family offers a selection of LED drivers with lower output voltages in a range of convenient form-factors and wattages. The Xitanium Outdoor drivers are SELV (Safety Extra Low Voltage) compliant, enabling easy LED light engine design. Xitanium Constant Voltage Outdoor LED drivers deliver a highly stable output voltage and are UL Class 2 rated. These drivers are the perfect choice for enabling easy modular connection of multiple LED PCBs in parallel. The Constant Voltage Outdoor category offers excellent reliability and ensures a simplified installation process. Robust design reduces maintenance and lowers the cost of ownership over the application lifetime. For optimal performance, LED luminaires require reliable drivers which match the long lifetime of the LEDs.

### Product data

#### • Operating Characteristics

|                           |               |
|---------------------------|---------------|
| Efficiency Range          | 98 %          |
| Output Power Range        | 100 W         |
| Input Power max           | 100 W         |
| Output Voltage Range      | 12-24 V       |
| Output Current Range (mA) | 5000          |
| Dimming range             | 100-0 %       |
| Input Current max         | 5000 (max) mA |
| Input Voltage Range (DC)  | 12-24 V       |
| Type of Dimming           | 0-10V         |

#### • Wiring Characteristics

|                     |          |
|---------------------|----------|
| Input Wire Length   | 177.8 mm |
| Control Wire Length | 177.8 mm |
| Output Wire Length  | 152.4 mm |
| Input wire AWG      | 18       |
| Output wire AWG     | 18       |
| Control wire AWG    | 22       |

#### • Temperature Characteristics

|           |                       |
|-----------|-----------------------|
| T-ambient | -40 (min), 60 (max) C |
|-----------|-----------------------|

#### • Product Dimensions

|                         |          |
|-------------------------|----------|
| Length A1               | 132.0 mm |
| Length A2               | 122.5 mm |
| Width B1                | 34.2 mm  |
| Height C1               | 25.0 mm  |
| Fixing Hole Diameter D1 | 3.8 mm   |

|                      |         |
|----------------------|---------|
| Fixing Hole Distance | 24.6 mm |
| Width B2             |         |
| Height C2            | 3.0 mm  |


#### • Approval & Application Chars

|                        |                   |
|------------------------|-------------------|
| ENEC certificate       | No                |
| CE marking             | Yes               |
| RoHS compliance        | Yes               |
| UL certificate         | Yes               |
| CSA certificate        | Yes               |
| Overload               | Protected         |
| No-load                | Protected         |
| EMI                    | FCC 47 subpart 15 |
| Environmental standard | UL Damp & Dry     |

#### • Product Data

|                             |  |
|-----------------------------|--|
| Order code                  | 913710830902                             |
| Full product code           | 913710830902                             |
| Full product name           | Xitanium 0-10V 12-24V DIMMING CONTROLLER |
| Order product name          | Xitanium 0-10V 12-24V DIMMING CONTROLLER |
| Pieces per pack             | 1  |
| Packing configuration       | 10                                       |
| Packs per outerbox          | 10                                       |
| Bar code on pack - EAN1     | 50781087062499                           |
| Bar code on outerbox - EAN3 | 50781087062499                           |
| Logistic code(s) - 12NC     | 913710830902                             |
| Net weight per piece        | 0.123 kg                                 |

Dimensional drawing



Xtanium LED drivers outdoor (Dimmable) slim outdoor leaded

| Product                         | A1 (Norm) | A2 (Norm) | A4 (Norm) | B1 (Norm) | B2 (Norm) | C1 (Norm) | C2 (Norm) | D1 (Norm) |
|---------------------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 0-10V 12-24V DIMMING CONTROLLER | 132.0     | 122.5     | -         | 34.2      | 24.6      | 25.0      | 3.0       | 3.8       |

