

Project Name

Location

Prepared By



Notes

(www) 07-30-2023 09:34:49

General	
Status	Active
Watts	9W
Fluorescent Equivalent	26W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	G24q-4 (4-Pin)
ANSI Base	G24q-4
Finish	White
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Temperature	Warm White to Natural Light
CRI	80+
Lumens	1100L
Beam Spread	120
Hours Rated	50000
Product Category	PL 4-Pin
Operating Position	Universal
Technology	LED

Electrical	
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Note	Only Dimmable with Compatible Dimming Ballasts
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	6.76
MOD	2.36
Housing Color	White
Weight (lb.)	0.4

Additional Information	
Installation Notes	Suggested wattage equivalency = 26W CFL
Rated For Enclosed Fixture	No
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp