

Project Name

Location

Prepared By



**Notes**

**General**

Watts	9
Fluorescent Equivalent	See Notes
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frosted
CCT (Kelvin)	2700
Temperature	Warm White
CRI	82
Lumens	900
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Burning Position	Horizontal Operation
Technology	LED

**Electrical**

Ballasting Requirements	Ballast By-pass; Direct wire voltage range 100-277V
Operating Frequency	50/60Hz
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

**Physical**

MOL	6.63
MOD	1.09

**Additional Information**

Additional Info	In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13; 18; and 26 watt CFLs
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Warranty	5 Year Limited

**Compliance**

Safety Listing	cULus Classified - Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED_Lamp