



LED LAMPS

ProLED[®] **Filament LED Series**

The look and feel of period-style incandescent through state-of-the-art LED technology



Contact Your Customer Care Specialist
For Pricing, Orders And Technical Support.
800.677.3334 www.halcolighting.com


ProLED® Filament LED Series

Product #: _____ Type: _____
 Project: _____ Date: _____
 Comments: _____ Initials: _____



A19 Clear A19 Amber A19 Frosted

A19



A15 Clear A15 Amber

A15



S14 Clear

S14 Amber

ST14

ST19 Clear

ST19 Amber

ST19 E26

Specifications

A Shapes

- 40W and 60W Equivalent options
- Clear 2700K and 3000K options
- Frosted 2700K finish options recreate the look of incandescent
- Amber 2200K creates a nostalgic look and feel
- Dimmable to 5%
- Curved Filament option offers stylish and unique design alternative

S14

- Replaces 25W incandescent
- Ideal for outdoor string lighting applications
- 2200K amber and 2700K clear options
- Dimmable and non-dimmable options

ST19

- Iconic antique shape ideal for hospitality
- 40W, 60W, 75W, and 100W equivalent options
- Clear 2700K and Amber 2200K options
- Dimmable to 5%
- Curved filament option offers stylish and unique design alternative
- Not recommended for outdoor use

Ordering Information



	Watt	Base	Product #	Product Code	Description	Dimmable	Volts	Color Temp.	CRI	Lumens	Useful Life*	Pkg. Qty.	MOL	Equivalent Wattage
A19														
⊕	5	E26	85037	A19CL5ANT/827/LED2	Clear Filament	Yes	120	2700K	82	450	15,000	10/60	4.13"	40
⊕	5	E26	85038	A19AMB5ANT/820/LED2	Amber Filament	Yes	120	2000K	82	340	15,000	10/60	4.13"	40
⊕	9	E26	85039	A19CL8ANT/827/LED2	Clear Filament	Yes	120	2700K	82	800	15,000	10/60	4.13"	60
⊕	9	E26	85040	A19FR8ANT/827/LED2	Frosted Filament	Yes	120	2700K	82	800	15,000	10/60	4.13"	60
⊕	9	E26	85041	A19AMB8ANT/820/LED2	Amber Filament	Yes	120	2000K	82	600	15,000	10/60	4.13"	60
⊕	6	E26	85078	A19AMB6ANT/820/CF/LED2	Clear Filament	Yes	120	2000K	82	450	15,000	10/60	4.13"	40
A15														
⊕	5	E26	85035	A15CL5ANT/827/LED2	Clear Filament	Yes	120	2700K	82	450	15,000	10/100	3/17"	40
⊕	6	E26	85036	A15AMB5ANT/820/LED2	Amber Filament	Yes	120	2000K	82	340	15,000	10/100	3/17"	40
S14														
⊕	2	E26	81139	S14CL2ANT/827/LED	Clear Filament	No	120	2700K	82	200	15,000	25/100	3.46"	25
⊕	2	E26	81140	S14AMB2ANT/822/LED	Amber Filament	No	120	2700K	82	160	15,000	25/100	3.46"	25
⊕	2	E26	82139	S14CL2ANT/827/LED2	Clear Filament	Yes	120	2700K	82	200	15,000	25/100	3.46"	25
⊕	2	E26	82140	S14AMB2ANT/822/LED2	Amber Filament	Yes	120	2700K	82	160	15,000	25/100	3.46"	25
ST19														
⊕	5.5	E26	85043	ST19CL5ANT/827/LED2	Clear Filament	Yes	120	2700K	82	500	15,000	10/60	5.79"	60
⊕	5.5	E26	85044	ST19AMB5ANT/822/LED2	Amber Filament	Yes	120	2200K	82	400	15,000	10/60	5.79"	40
⊕	7	E26	85045	ST19CL7ANT/827/LED2	Clear Filament	Yes	120	2700K	82	800	15,000	10/60	5.79"	100
⊕	7	E26	85046	ST19AMB7ANT/822/LED2	Amber Filament	Yes	120	2200K	82	650	15,000	10/60	5.79"	60
⊕	6.5	E26	85080	ST19AMB6ANT/820/CF/LED2	Amber Filament	Yes	120	2000K	82	450	15,000	10/60	5.79"	40
⊕	7.5	E26	85089	ST19CL7ANT/830/LED2	Clear Filament	Yes	120	3000K	82	800	15,000	10/60	4.9"	60

⊕ NEW ITEM

* Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels. Represents lamps that are ENERGY STAR® certified. Warranty Commercial/Industrial: This product is warranted for 3 years from the date purchase. Not for use in enclosed fixtures. May not be compatible with all dimmable systems, dimming performance may vary by system, please check the website www.halcolighting.com for up-to-date dimmer compatibility information. Use on incompatible systems may shorten lamp life.