

Model Number AC25CD700AT2Q

Input Voltage: 120-277VAC (±10%) Dimming: 5 to 100%
Input Frequency: 50/60Hz Surge Protection: 2Kv
Side Mount/Leads Multi-Switching Current

PHYSICAL:

Dimensions	
Length	2.88"
Width	1.43"
Height	1.07"
Mounting	2.68"
Weight	0.15 lbs.

"Match-Book Sized"
LED Driver Family

The Smallest Possible Form Factors™




Actual Size

ELECTRICAL SPECIFICATIONS:

Output Power Max.	Input Power	Input Current	Minimum PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Minimum Starting Temp.	IP Rating	Dimming Protocol	Dimming Range	Efficiency Up To
25.2W	28.6W	0.27A@120V 0.11A@277V	>0.9	<20	24-36V	700mA±5%	75° C	0° C	20	0 to 10V	5 to 100%	88%
18W	20.5W	0.19A@120V 0.08A@277V	>0.9	<20	24-36V	500mA±5%	75° C	0° C	20	0 to 10V	5 to 100%	88%
12.6W	14.7W	0.14A@120V 0.06A@277V	>0.9	<20	24-36V	350mA±5%	75° C	0° C	20	0 to 10V	5 to 100%	86%

WIRING:



Lead Lengths

Black	6"	Blue	6"	Purple	6"
White	6"	Red	6"	Gray	6"

Approved Dimmers

Lutron	NTSTV-DV	Leviton	IP710 DL
Lutron	NFTV	Watt Stopper	ADF I20277

SAFETY & PERFORMANCE:

- Class P Listed
- Class A sound rating
- No PCBs
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- Warranty: 5 yrs based on max case temp of 75°C*
- Input/Output Isolation
- Surge Protection (2 KV)
- Dimming Curve on the next page

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- 22 AWG 600V/I05C tinned stranded copper lead-wires are required to use in installation
- Max Remote installation distance is 33 ft



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years from date of manufacture when operated at max case temp of up to ≤75°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

