



RSS Rapid Start High Output Fluorescent Ballasts

*For T-12 and T-8 High Output Lamps.
2' to 10' Lamp Operation.*



Allanson's RSS Ballasts combine solid-state technology with magnetic ballast wiring.

- Five RSS Ballasts replace 15 existing models for less inventory and increased savings
- Rapid cold weather start at -30°C
- Meets FCC Rating, low RFI and EMI ensures no interference issues
- Meets ANSI C82.11 Standards
- Less than 8% THD for installation confidence
- Quiet operation in all installation conditions, sound rated 'A'
- Thermal protection
- Increased lamp life
- New smaller profile allows for greater adaptability for low profile signage menu board applications



RSS BALLAST-07-12



Fluorescent

RSS Rapid Start High Output Fluorescent Ballasts

Specifications								
Catalog #	Number of Fluorescent Lamps	Input Line Current	Min. Start Temp.	Input Voltage	Open circuit Voltage	Lamp Footage	High Power Factor	Dims
RSS196AT	1-F96T8HO/86W	1.00	-30°C (-20°F)	120v 50/60Hz	825V	Min 2' Max 8'	> 0.98	L: 9 1/2" W: 2 11/32" H: 1 11/16"
	1-F96T12HO/110W	0.85						
	1-F72T8HO/65W	0.75						
	1-F24T12HO/37W	0.32						
RSS296AT	2-F96T12HO/110W	1.60	-30°C (-20°F)	120v 50/60Hz	950V	Min 4' Max 12' (T8) Max 16' (T12)	> 0.98	L: 11 3/4" W: 2 5/32" H: 1 5/8"
	2-F72T8HO/65W	1.45						
	1-F120T12HO/135W	1.10						
	1-F96T8HO/86W	1.05						
	1-F96T12HO/110W	0.90						
RSS396AT	3-F96T12HO/110W	2.20	-30°C (-20°F)	120v 50/60Hz	950V	Min 8' Max 18' (T8) Max 24' (T12)	> 0.98	L: 11 3/4" W: 3 3/16" H: 1 25/32"
	3-F72T8HO/65W	2.15						
	2-F120T12HO/135W	2.00						
	2-F96T8HO/86W	1.90						
	2-F96T12HO/110W	1.65						
	2-F72T8HO/65W	1.60						
RSS496AT	4-F96T12HO/110W	3.20	-30°C (-20°F)	120v 50/60Hz	950V	Min 8' Max 24' (T8) Max 32' (T12)	> 0.98	L: 14 7/16" W: 3 3/16" H: 2 5/8"
	4-F72T8HO-65W	2.55						
	3-F96T12HO/110W	2.30						
	2-F120T12HO/135W	2.30						
	2-F96T8HO/86W	2.20						
	2-F96T12HO/110W	1.75						
RSS696AT	6-F96T12HO/110W	4.15	-30°C (-20°F)	120v 50/60Hz	950V	Min 18' (T8) Min 24' (T12) Max 36' (T8) Max 48' (T12)	> 0.98	L: 16 1/2" W: 3 3/16" H: 2 5/8"
	6-F72T8HO/65W	4.10						
	4-F120T12HO/135W	3.96						
	4-F96T8HO/86W	3.80						
	5-F96T12HO/110W	3.65						
	4-F96T12HO/110W	3.20						

RSS Ballast Footage Chart																										
CAT#	T8/T12	# of Lamps	Total Lamp Footage Range (Feet)																							
			2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48
RSS196AT	T8	1																								
	T12	1																								
RSS296AT	T8	1,2																								
	T12	1,2																								
RSS396AT	T8	2,3																								
	T12	2,3																								
RSS496AT	T8	2,3,4																								
	T12	2,3,4																								
RSS696AT	T8	4,5,6																								
	T12	4,5,6																								

Visit us at www.allanson.com

US
Phone 1.800.559.3659
Fax 1.615.643.1890
Email customerservice@eballast.com

CANADA
1.800.661.7251
1.416.752.6717
custserv@allanson.com



Fluorescent