















# T3-1/4 (9mm) Miniature Based LED Lamps

Miniature Packages	Replaces Incandescent	Part Number	Electrical-Optical Characteristics (Ta = 25°C)			Angle of Illumination	Special Features
			Voltage V typ	Current mA typ	Intensity mcd		
<b>595nm Super Yellow InGaAlP</b>  <b>BF321</b> 	<b>T3-1/4 (9mm) Miniature Bayonet</b>	6MB, 44, 47, 755	BF321-0UY-006B	5/6V	20	116	120°  Center Contact Polarity B = Bipolar AC/DC A = AC only  Replace BF321 With B321 for Narrow Beam (15°) 3.2K mcd @ 20mA
		12MB, 756	BF321-0UY-014B	12/14V	20	116	
		24MB,	BF321-0UY-024B	24V	20	116	
		313,757,1819,1829	BF321-0UY-028B	28V	20	116	
		48MB	BF321-0UY-048B	48V	12	54	
		60MB,1835	BF321-0UY-060B	60V	12	54	
		120MB, NE51H	BF321-0UY-120A	120VAC	10	39	
	BF321-0UY-130B	130V	8	24			
<b>595nm Super Yellow InGaAlP</b>  <b>BF304</b> 	<b>T3-1/4 (9mm) Miniature Bayonet LED Cluster</b>	6MB, 44, 47, 755	BF304-0UY-006B	5/6V	80	464	120°  Center Contact Polarity B = Bipolar AC/DC A = AC only  Replace BF304 With B304 for Narrow Beam (15°) 12.8K mcd @ 20mA
		12MB, 756	BF304-0UY-014B	12/14V	40	464	
		24MB,	BF304-0UY-024B	24V	20	464	
		313,757,1819,1829	BF304-0UY-028B	28V	20	464	
		48MB	BF304-0UY-048B	48V	12	216	
		60MB,1835	BF304-0UY-060B	60V	12	216	
		120MB, NE51H	BF304-0UY-120A	120VAC	10	156	
	BF304-0UY-130B	130V	8	96			
<b>595nm Super Yellow InGaAlP</b>  <b>BF3126/ BF3127</b> 	<b>T3-1/4 (9mm) Miniature Bayonet LED Cluster</b>	6MB, 44, 47, 755	BF3126-0UY-006B	5/6V	120	192	120°  Center Contact Polarity B = Bipolar AC/DC A = AC only  Replace BF3126/3127 With B3126/3127 for Medium Beam (50°) 7K mcd @ 20mA
		12MB, 756	BF3126-0UY-014B	12/14V	40	192	
		24MB,	BF3127-0UY-024B	24V	20	224	
		313,757,1819,1829	BF3127-0UY-028B	28V	20	224	
		48MB	BF3127-0UY-048B	48V	12	105	
		60MB,1835	BF3127-0UY-060B	60V	12	105	
		120MB, NE51H	BF3127-0UY-120A	120VAC	10	87	
	BF3127-0UY-130B	130V	8	70			
<b>8000K Cool White SiC/GaN</b>  <b>BF321</b> 	<b>T3-1/4 (9mm) Miniature Bayonet</b>	6MB, 44, 47, 755	BF321-0CW-006B	5/6V	15	160	120°  Center Contact Polarity B = Bipolar AC/DC A = AC only  Replace BF321 With B321 for Std. Beam (50°)
		12MB, 756	BF321-0CW-014B	12/14V	15	160	
		24MB,	BF321-0CW-024B	24V	15	160	
		313,757,1819,1829	BF321-0CW-028B	28V	15	160	
		48MB	BF321-0CW-048B	48V	12	128	
		60MB,1835	BF321-0CW-060B	60V	12	128	
		120MB, NE51H	BF321-0CW-120A	120VAC	10	106	
	BF321-0CW-130B	130V	8	85			
<b>8000K Cool White SiC/GaN</b>  <b>BF304</b> 	<b>T3-1/4 (9mm) Miniature Bayonet LED Cluster</b>	6MB, 44, 47, 755	BF304-0CW-006B	5/6V	60	640	120°  Center Contact Polarity B = Bipolar AC/DC A = AC only  Replace BF304 With B304 for Std. Beam (50°)
		12MB, 756	BF304-0CW-014B	12/14V	30	640	
		24MB,	BF304-0CW-024B	24V	15	640	
		313,757,1819,1829	BF304-0CW-028B	28V	15	640	
		48MB	BF304-0CW-48B	48V	12	512	
		60MB,1835	BF304-0CW-60B	60V	12	512	
		120MB, NE51H	BF304-0CW-120A	120VAC	10	424	
	BF304-0CW-130B	130V	8	340			
<b>8000K Cool White SiC/GaN</b>  <b>BF3126/ BF3127</b> 	<b>T3-1/4 (9mm) Miniature Bayonet LED Cluster</b>	6MB, 44, 47, 755	BF3126-0CW-006B	5/6V	90	900	120°  Center Contact Polarity <b>B = Bipolar AC/DC</b> A = AC only  Replace BF3126/3127 With B3126/3127 for Std. Beam (50°)
		12MB, 756	BF3126-0CW-014B	12/14V	30	900	
		<b>24MB,</b>	<b>BF3126-0CW-024B</b>	<b>24V</b>	<b>15</b>	<b>900</b>	
		313,757,1819,1829	BF3127-0CW-028B	28V	15	1050	
		48MB	BF3127-0CW-048B	48V	12	840	
		60MB,1835	BF3127-0CW-060B	60V	12	840	
		120MB, NE51H	BF3127-0CW-120A	120VAC	10	700	
	BF3127-0CW-130B	130V	8	560			

All dimensions in inches. For millimeters multiply by 25.4

Log # 122J Rev 10-2000