



Tango G4 LED Flood

BVP431 LED135/CW 220~240V 100W SWB GM

Tango G4 LED Flood, 13500 lm, 100 W, 757 cool white, Safety class I

Philips Tango G4 LED flood lighting is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

Warnings and Safety

- please pay attention to the mounting instructions

Product data

General Information		Light source color	
Driver included	Yes	757 cool white	
Service tag	Yes	Operating and Electrical	
Lighting Technology	LED	Input Voltage	220 to 240 V
Light Technical		Line Frequency	50 or 60 Hz
Luminous Flux	13,500 lm	Power Consumption	100 W
Correlated Color Temperature (Nom)	5700 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	135 lm/W	Connection	Flying leads/wires
Color rendering index (CRI)	>70	Cable	Cable 1.5 m without plug
		Number of products on MCB of 16 A type B	18

Tango G4 LED Flood

Protection class IEC	Safety class I
----------------------	----------------

Controls and Dimming

Dimmable	No
Control interface	-

Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Housing Color	Gray
Overall length	265 mm
Overall width	419 mm
Overall height	79 mm
Dimensions (Height x Width x Depth)	79 x 419 x 265 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Polycarbonate bowl/cover
Net Weight (Piece)	4.430 kg

Approval and Application

CE mark	Yes
---------	-----

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	BVP431 LED135/CW 220~240V 100W SWB GM
Full product name	BVP431 LED135/CW 220~240V 100W SWB GM
Full product code	871951452444600
Order code	52444600
Material Nr. (12NC)	911401683506
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514524446
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514524446

