



Ledinaire High-bay

BY030P LED150_220_280S/840_50_65 PSU WB

Ledinaire High-bay, All-in, 195 W, 145 W, 100 W, ϕ 320 mm, 15000 lm, 22000 lm, 28000 lm, 4000 K, 5000 K, 6500 K, Symmetrical, IP65, IK07

The Ledinaire highbay range contains a selection of off-the-shelf highbay LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire highbay enables, simple and flexible installation, either on a hook, or optional bracket. Products can be installed with optional reflectors for lower glare.

Product data

General Information		Optic type	
Number of gear units	1 unit	Optic type	Symmetrical
Driver included	Yes	Luminaire light beam spread	90°
Value ladder	Value	Unified glare rating CEN	31
Serviceability class	Class C, luminaire without serviceable parts, not serviceable	All-in Type	All-in, Multi Lumen All-in, Multi Color Temperature
Warranty period	5 years	Operating and Electrical	
Sustainability rating	-	Input Voltage	220 to 240 V
Light Technical		Line Frequency	50 or 60 Hz
Luminous Flux	15,000 22,000 28,000 lm	Inrush current	68 A
Saturated Red (R9)	<50	Inrush time	0.213 ms
Correlated Color Temperature (Nom)	4000 5000 6500 K	Power Consumption	195 145 100 W
Luminous Efficacy (rated) (Nom)	152 142 lm/W	Power Factor (Fraction)	0.9
Color rendering index (CRI)	>80	Connection	Screw connector
Light source color	840 neutral white, neutral white and 865 cool daylight	Cable	Cable 0.3 m with connector 3-pole
		Number of products on MCB of 16 A type B	9
		Suitable for random switching	No

Ledinaire High-bay

Protection class IEC	Safety class I
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit
Control interface	-
Constant light output	No
Embedded control	-
Photocell	-

Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	Aluminum and black
Optical cover finish	Clear
Reflector Finish	-
Overall height	119 mm
Overall diameter	320 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Mounting	Suspended
Net Weight (Piece)	2.460 kg

Emergency Operation

Central Emergency	No
-------------------	----

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C

Flickering value (PstLM) - Flickering value as 1 per EN 61000-3-3

Stroboscopic effect visibility measure (SVM)	0.9
Ambient temperature range	-30 to +50 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.38, 0.38); (0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Control gear failure rate at median useful life 75000 h	15 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	L65

Product Data

Order product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product code	872016975897100
Order code	911401822687
Material Nr. (12NC)	911401822687
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169758971
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169758971

Ledinaire High-bay

Dimensional drawing

BY030P LED150_220_280S/840_50_65 PSU WB

