

Job / Project Name	
Product Model Number	
Quantity	
Date	

APPLICATIONS

Warehouse and manufacturing factories, outdoor post tops, bollards, commercial and residential recessed cans, and institutional and educational facilities.

PRODUCT FEATURES

- **Wattages:** 30W, 40W, 50W, 65W, 85W, 105W, 135W
- **Color Temperatures:** 50K (standard), 30K, 40K, 60K, (special order)
- **Efficacy:** 155 lm/W
- **Voltage Input:** 100-277VAC, 480VAC for all except 30W & 105W
- **CRI:** >80Ra
- **Base Type:** E26, E39
- **Operating Temperature:** -4 to 122F
- **LED Lifespan:** 50,000 hours
- **Beam Angle:** 360 degrees
- **Warranty:** 5 years
- **Built-in Surge Protection:** 4KV



RETROFIT EXISTING FIXTURES



SPECIFICATIONS

PRODUCT #	WATTAGES	DIMENSIONS (WxL)	LUMENS (+/-10%)	SUGGESTED HID EQUIV.	CERT.	480VAC
C-E26-30-50K-STUB	30W	4.17" x 6.30"	4,650	175-200W	ETL	N/A
C-E39-30-50K-STUB	30W	4.17" x 6.69"	4,650	175-200W	ETL	N/A
C-E26-40-50K-STUB	40W	4.17" x 6.30"	6,200	200-250W	ETL, DLC	Yes
C-E39-40-50K-STUB	40W	4.17" x 6.69"	6,200	200-250W	ETL, DLC	Yes
C-E26-50-50K-STUB	50W	4.17" x 6.30"	7,750	250-300W	ETL, DLC	Yes
C-E39-50-50K-STUB	50W	4.17" x 6.69"	7,750	250-300W	ETL, DLC	Yes
C-E26-65-50K-STUB	65W	4.17" x 6.50"	10,075	250-350W	ETL, DLC	Yes
C-E39-65-50K-STUB	65W	4.17" x 6.89"	10,075	250-350W	ETL, DLC	Yes
C-E26-85-50K-STUB	85W	4.17" x 6.50"	13,175	400-500W	ETL, DLC	Yes
C-E39-85-50K-STUB	85W	4.17" x 6.89"	13,175	400-500W	ETL, DLC	Yes
C-E39-105-50K-STUB	105W	4.17" x 9.65"	16,275	400-600W	ETL, DLC	Yes
C-E39-135-50K-STUB	135W	5.20" x 9.45"	20,925	400-800W	DLC	Yes

NOTE: DLC for approved fixture categories and only with E39 base.

PRODUCT BUILDER

Ex: C-E26-30-50K-STUB

C	-		-		-		=	
Type		Base		Wattage		Color Temperature		Product
		E26		30W		50K (standard)		STUB
		E39		40W		60K		
				50W		40K		
				65W		30K		
				85W				
				105W				
				135W				
								Voltage Input
								480VAC

Specifications and actual product may vary.