

C023 C034

LED Vapor Tight



Features

Housing

Injection Molded Polycarbonate Housing and Shade
 Ideal for Harsh Environment Applications
 Suitable for Ceiling Mount or Wall Mount

Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity

Electrical

Built-in Constant Current LED Driver with High Efficient LED Module
 Built-in Emergency Battery Backup (-EM)
 Bi-Level Light with Built-in High Frequency Motion Sensor (-BI)

Lamp

Built-in LED Module, Color Temperature Option 3000K, 3500K, 4000K, 5000K

Certification

ETL/cETL Listed, Wet Location Rated, Energy Star Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen/CT (TYP)	Lumen at the Source /CT (TYP)	Dimension (OD X H)	Energy Star
C023-65-xxxxK	120V ~ 277V	23W	>80	1620 / 3000K	2200 / 3000K	14.3" x 5.7"	Yes
C034-65-xxxxK	120V ~ 277V	34W	>80	2380 / 3000K	3300 / 3000K	17.7" x 5.7"	Yes