



Combination Series – CC

THERMOPLASTIC EXIT/EMERGENCY COMBO



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____

PRODUCT DESCRIPTION

The CC thermoplastic LED Exit/Emergency combination unit with Adjustable Heads offers tremendous flexibility. The emergency lighting heads can be rotated from a side-mount configuration to a top-mount configuration in one simple motion. Possessing premium installation features such as a snap-fit canopy & housing, along with push-out chevron directional indicators, the CC offers unsurpassed value in an aesthetically pleasing design. All CC signs include a second faceplate and a snap-fit canopy for universal installation.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Injection molded, engineering-grade, UV-stable thermoplastic • UL94V-0 flame rating • Impact, scratch, fade and corrosion-resistant • Durable unibody housing frame with reinforcing ribs and integral wiring channel • Snap-fit faceplate and backplate • Second faceplate included for double face applications • 6" letters with 3/4" stroke width • Full-size, 3/4" wide chevron directional indicators • Chevron directional indicators can be easily removed or reinserted as necessary • Red or green letters • White or black textured finish.

ELECTRICAL

Dual voltage 120/277VAC • Rated for use in damp locations • Solid state charging and switching • Brownout protection • Battery low voltage disconnect • Overload and short circuit protection • AC power indicator and test switch.

LAMPS

Long life, energy saving LED lamps • Exit sign LEDs are single color (red or green) and connected in a series/parallel configuration such that the unlikely failure of one LED will affect no more than one other LED.

HEADS

Includes two 6V, 5.4W lighting heads • Contemporary square head design • Heads rotate a full 360° in all directions for comprehensive lighting coverage.

BATTERY


Sealed, maintenance-free 6V lead calcium • Standard battery will operate sign and two 5.4W heads for a minimum of 90 minutes in the event of a power outage • High Output (REM option) version will operate the sign and two 5.4W heads plus an additional 12W remote load for a minimum of 90 minutes.

CODE COMPLIANCE

ETL Listed to UL924 standards • Damp location rated • NFPA 101 Life Safety Code compliant • NEC and OSHA compliant • Meets the State of Minnesota energy efficiency requirements.

WARRANTY

5-year warranty. Product specifications subject to change without notice.



INSTALLATION

MOUNTING

May be top or back mounted • All signs include quick-install snap-fit canopy and mounting hardware for easy top mount installation • Backplate includes universal mounting pattern knockouts for simple back mounting.



ORDERING INFORMATION

model	letter color	# of faces	housing color	options	accessories
CC	R = Red G = Green	U ¹ = Universal	W = White B = Black	SD = Self Diagnostics REM ² = Remote Capacity IRT = Infrared Remote Testing	VRS2 = Poly Guard (back mount) WG1 = Wire Guard (back mount)

Notes

¹Universal includes 2nd exit face, backplate and canopy

²will operate the sign and two 5.4W heads plus an additional 6V 12W remote load

Ordering Example CC-R-U-W-SD



Combination Series – CC



THERMOPLASTIC EXIT/EMERGENCY COMBO



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____

PHOTOMETRICS

6V, 5.4W Tungsten Wedge Base Lamp (ANSI 939), Square Head



BATTERY DATA

- Lead Calcium battery warranted for one full year with additional 4 years pro-rated warranty
- Recharges in 24 hours or less

Type	Battery Voltage	Shelf Life ¹	Expected Life ¹	Temperature Range ²
Lead Calcium (Std.)	6V, 4.5Ah	15 months	5-8 years	40°F-95°F
Lead Calcium (D7?)	Two 6V,4.5Ah	15 months	5-8 years	40°F-95°F

¹ At 77°F

² To obtain rated life and capacity.

ENGINEERING DATA

	Input Voltage	Max. Amps	Max. Watts	Standby Watts*
Red LED	120	0.06	6.5	3.6
Red LED	277	0.03	6.8	3.7
Green LED	120	0.06	7.1	4.2
Green LED	277	0.03	7.4	4.2
Red LED - REM Option	120	0.12	14.3	4.4
Red LED - REM Option	277	0.06	14.7	4.4
Green LED - REM Option	120	0.13	14.7	4.4
Green LED - REM Option	277	0.06	14.9	4.4

* Fully charged battery

LED REMOTE HEADS (ORDER SEPERATELY)

- Each lamp contains 12 long-life, efficient ultra-bright white LED's
- Available in Single or Double head configurations
- Indoor or Outdoor ratings available

MODEL	DESCRIPTION
ASRLED-1	Single LED Remote Indoor
ASRLED-2	Double LED Remote Indoor
ASRLED-1-SD	Single LED Remote Indoor (Units w/ SD Option)
ASRLED-2-SD	Double LED Remote Indoor (Units w/ SD Option)
ASRLED-1-WP	Single LED Remote Outdoor
ASRLED-2-WP	Double LED Remote Outdoor
ASRLED-1-WP-SD	Single LED Remote Outdoor (Units w/ SD Option)
ASRLED-2-WP-SD	Double LED Remote Outdoor (Units w/ SD Option)

OUTDOOR REMOTE HEADS



INDOOR REMOTE HEADS

