



## ProLume Reflectors

ProLume® Reflector Series has maximum light distribution achieved through compact design.

ProLume CFL Reflectors save up-to 77% in energy costs compared to incandescent lamps. ProLume Reflector Lamps have a tri-phosphor coating that enhances lumen efficacy and color rendering, 82 CRI.

### Specifications:

- Contains amalgam
- E26 base and GU24 base
- Electronic instant start ballast
- Minimum starting temperature -20°F
- Dimmable R30, R40 and PAR30
- 11 to 23 watts
- BR38, R20, R30, R40, PAR20, PAR30 and PAR38 shapes
- R30 Colors Blue, Green, Pink and Yellow
- 8,000-10,000 Hours Average Rated Life

- » Saves energy
- » Amalgam technology maintains light output in extreme temperatures
- » Low maintenance

### Markets:

- Residential
- Commercial

### Applications:

- Track lighting
- Down lighting
- General lighting



## Ordering Information

| Bulb Type               | Watts | Base | Product # | Product Code       | Description               | Pkg. Qty. | Color Temp. | CRI | Initial Lumens | Incandescent Equivalent | Avg. Rated Life | MOL (In) |
|-------------------------|-------|------|-----------|--------------------|---------------------------|-----------|-------------|-----|----------------|-------------------------|-----------------|----------|
| <b>PAR20 &amp; R20</b>  |       |      |           |                    |                           |           |             |     |                |                         |                 |          |
| PAR20                   | 11    | Med. | 46005     | CFL11/27/PAR20     | Warm White Flood          | 6/24      | 2700        | 82  | 380            | 50                      | 10000           | 3.86"    |
| PAR20                   | 11    | Med. | 46006     | CFL11/35/PAR20     | White Flood               | 6/24      | 3500        | 82  | 380            | 50                      | 10000           | 3.86"    |
| PAR20                   | 11    | Med. | 46007     | CFL11/41/PAR20     | Cool White Flood          | 6/24      | 4100        | 82  | 380            | 50                      | 10000           | 3.86"    |
| PAR20                   | 11    | Med. | 46008     | CFL11/50/PAR20     | Natural White Flood       | 6/24      | 5000        | 82  | 380            | 50                      | 10000           | 3.86"    |
| R20                     | 11    | GU24 | 46542     | CFL11/27/R20/GU24  | Warm White Flood          | 6/24      | 2700        | 82  | 340            | 50                      | 10000           | 4.02"    |
| R20                     | 14    | Med. | 46011     | CFL14/30/R20       | Soft White Flood          | 6/24      | 3000        | 82  | 500            | 50                      | 8000            | 4.94"    |
| R20                     | 14    | Med. | 46014     | CFL14/50/R20       | Natural White Flood       | 6/24      | 5000        | 82  | 500            | 50                      | 8000            | 4.94"    |
| <b>PAR30 &amp; R30</b>  |       |      |           |                    |                           |           |             |     |                |                         |                 |          |
| PAR30                   | 15    | Med. | 46001     | CFL15/27/PAR30     | Warm White Flood          | 6/24      | 2700        | 82  | 750            | 75                      | 10000           | 4.60"    |
| PAR30                   | 15    | Med. | 46550     | CFL15/27/PAR30/DIM | Warm White Dimmable Flood | 6/24      | 2700        | 82  | 750            | 75                      | 10000           | 4.60"    |
| PAR30                   | 15    | Med. | 46002     | CFL15/35/PAR30     | White Flood               | 6/24      | 3500        | 82  | 750            | 75                      | 10000           | 4.60"    |
| PAR30                   | 15    | Med. | 46003     | CFL15/41/PAR30     | Cool White Flood          | 6/24      | 4100        | 82  | 750            | 75                      | 10000           | 4.60"    |
| PAR30                   | 15    | Med. | 46004     | CFL15/50/PAR30     | Natural White Flood       | 6/24      | 5000        | 82  | 750            | 75                      | 10000           | 4.60"    |
| R30                     | 15    | GU24 | 46538     | CFL15/27/R30/GU24  | Warm White                | 6/24      | 2700        | 82  | 750            | 65                      | 10000           | 4.76"    |
| R30                     | 15    | Med. | 46328     | CFL15/27/R30/DIM   | Warm White Dimmable Flood | 6/24      | 2700        | 82  | 680            | 65                      | 8000            | 6.01"    |
| R30                     | 15    | Med. | 109056    | CFL15/BLU/R30      | Blue Flood                | 6/24      | -           | 82  | 720            | 65                      | 8000            | 5.10"    |
| R30                     | 15    | Med. | 109058    | CFL15/GRN/R30      | Green Flood               | 6/24      | -           | 82  | 720            | 65                      | 8000            | 5.10"    |
| R30                     | 15    | Med. | 109054    | CFL15/PNK/R30      | Pink Flood                | 6/24      | -           | 82  | 720            | 65                      | 8000            | 5.10"    |
| R30                     | 15    | Med. | 109062    | CFL15/YEL/R30      | Yellow Flood              | 6/24      | -           | 82  | 720            | 65                      | 8000            | 5.10"    |
| R30                     | 16    | Med. | 46101     | CFL16/30/R30/ES    | Soft White Flood          | 6/24      | 3000        | 82  | 750            | 65                      | 10000           | 5.60"    |
| R30                     | 16    | Med. | 46104     | CFL16/41/R30       | Cool White Flood          | 6/24      | 4100        | 82  | 750            | 65                      | 10000           | 5.60"    |
| R30                     | 16    | Med. | 46105     | CFL16/50/R30       | Natural White Flood       | 6/24      | 5000        | 82  | 750            | 65                      | 10000           | 5.60"    |
| <b>BR38 &amp; PAR38</b> |       |      |           |                    |                           |           |             |     |                |                         |                 |          |
| BR38                    | 23    | Med. | 109216    | CFL23/30/BR38      | Soft White Flood          | 6/24      | 3000        | 82  | 1300           | 100                     | 10000           | 6.40"    |
| PAR38                   | 23    | Med. | 46201     | CFL23/27/PAR38     | Warm White Flood          | 6/24      | 2700        | 82  | 1280           | 90                      | 10000           | 5.35"    |
| PAR38                   | 23    | Med. | 46202     | CFL23/35/PAR38     | White Flood               | 6/24      | 3500        | 82  | 1280           | 90                      | 10000           | 5.35"    |
| PAR38                   | 23    | Med. | 46203     | CFL23/41/PAR38     | Cool White Flood          | 6/24      | 4100        | 82  | 1280           | 90                      | 10000           | 5.35"    |
| PAR38                   | 23    | Med. | 46204     | CFL23/50/PAR38     | Natural White Flood       | 6/24      | 5000        | 82  | 1280           | 90                      | 10000           | 5.35"    |
| <b>R40</b>              |       |      |           |                    |                           |           |             |     |                |                         |                 |          |
| R40                     | 23    | Med. | 46329     | CFL23/27/R40/DIM   | Warm White Dimmable Flood | 6/24      | 2700        | 82  | 1090           | 100                     | 10000           | 6.97"    |
| R40                     | 23    | Med. | 109286    | CFL23/30/R40       | Soft White Flood          | 6/24      | 3000        | 82  | 1090           | 100                     | 10000           | 6.50"    |
| R40                     | 23    | Med. | 46206     | CFL23/50/R40       | Natural White Flood       | 6/24      | 5000        | 82  | 1090           | 100                     | 10000           | 6.50"    |
| R40                     | 23    | Med. | 46208     | CFL23/PB/R40       | Pool Bright Flood         | 6/24      | 6450        | 82  | 1000           | 90                      | 10000           | 6.50"    |

**Hg** Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.  
 Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.

Represents lamps that are ENERGY STAR approved.

CAUTION: Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors.

This device is not intended for use with emergency exit fixtures. Dimmable lamps may not be compatible with all dimmers.

This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.

WARRANTY - Commercial/Industrial: Dimmable lamps are warranted for 2 years from date of purchase based on 3 hours of use per day.

Non-dimmable lamps are warranted for 2 years from date of purchase based on 10 hours of use per day.