

ProLume® Dimmable

COMPACTS

Bulb Type	Watts	Base	Product #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Avg Rated Life	MOL (Inches)
A-LINE												
A19	14	Med.	46305	CFL14/27/A19/DIM	Warm White Dimmable	1/12	2700	82	800	60	10000	4.75"
SPIRALS												
⊕ T3	13	GU24	46544	CFL13/27/GU24/DIM	Warm White Dimmable	10/60	2700	82	800	60	10000	4.00"
T3	15	Med.	46330	CFL15/27/DIM	Warm White Dimmable	10/60	2700	82	950	60	10000	5.53"
⊕ T3	18	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	10/60	2700	82	1100	75	10000	4.40"
T3	23	Med.	46334	CFL23/27/DIM	Warm White Dimmable	10/60	2700	82	1600	100	10000	5.59"
⊕ T3	23	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	10/60	2700	82	1600	100	10000	4.85"
REFLECTORS												
⊕ PAR30	15	Med.	46550	CFL15/27/PAR30/DIM	Warm White Dimmable Flood	6/24	2700	82	750	65	10000	4.60"
R30	15	Med.	46328	CFL15/27/R30/DIM	Warm White Dimmable Flood	6/24	2700	82	680	65	8000	6.01"
R40	23	Med.	46329	CFL23/27/R40/DIM	Warm White Dimmable Flood	6/24	2700	82	1090	100	10000	6.97"

⊕ NEW ITEM!

(Hg) Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.
Visit www.lamprecycle.org for disposal information for your state or local government.



CAUTION: This device is not intended for use with emergency exit fixtures. Dimmable lamps may not be compatible with all dimmers. This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.

WARRANTY - Commercial/Industrial: This product is warranted for 2 years from the date of purchase, based on 3 hours of use per day.