

# CHLORIDE

by Signify



## Exit/Emergency

Caliber series

Architectural LED edge-lit  
special wording sign



Project: \_\_\_\_\_  
Location: \_\_\_\_\_  
Cat.No: \_\_\_\_\_  
Type: \_\_\_\_\_  
Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_  
Notes: \_\_\_\_\_

### Example: CSBR2RE17

#### CS

##### Series

CS - Caliber Series White LED AC Only Signage

##### Housing Color

A - Brushed Aluminum  
B - Black  
W - White  
BR - Dark Bronze

##### # of Faces

1 - Single Face  
2 - Double Face

##### Graphics Color

R - Red  
G - Green  
B - Blue  
K - Black  
Y - Yellow

Optional text colors available, consult factory.

##### Lens Insert

Blank - Clear  
M - Mirror

##### Special Wording

See Back Page or Consult Factory

##### Options

Blank - No Options  
FL - AC Flasher  
RFL - Remote Switched Flasher

### Accessories (Order Separately)

PKIT12W - Pendant Kit, 12" White Finish\*

PKIT12B - Pendant Kit, 12" Black Finish\*

\*Custom pendant lengths and colors available, consult factory.

### codes and standards

- UL 48 listed
- IC rated
- UL damp location listing 32°F (0°C) to 104°F (40°C)
- Meets ADA specifications for wall mounted lighting fixtures

### construction

- All housing components are premium die-cast aluminum construction.
- A range of finishes are available (see Ordering Information below).
- A bar hanger bracket kit is standard for recessed applications.

### installation

- Universal mounting configurations include recessed ceiling mount, surface ceiling mount, surface end mount and surface wall mount.
- Surface mount configurations mount to a 3.5" octagonal junction box.

### electronics

- AC only - 120/277 VAC dual voltage input with surge protection is standard on all models.

operating temperature range

- 32°F (0°C) to 104°F (40°C).

power consumption

- AC only, 120 VAC: 60 Hz, 0.084 A, 9.1 W, .90 Pf.
- AC only, 277 VAC: 60 Hz, 0.037 A, 9.3 W, .90 Pf.

### lamps

- Illumination of the Caliber Signage panel is accomplished with the use of high-brightness white LEDs in an optical array offering even illumination.

### warranty

- Five full year warranty on unit.




# CS Caliber series architectural LED edge-lite special wording sign

## options

- FL – This option enables the sign to operate in a 50% duty cycle flashing mode any time AC power is present. This option allows off or flashing operation.
- RFL – This option allows for an external, normally open, dry contact switch to control the flashing mode. This mode allows for off, on, or flashing operation.

## dimensions

6" surface ceiling mount



See Caliber Series for more dimensions and mounting examples.

## special wording examples (consult factory for additional options)



E2



E4



E6



E8




E11



E14




E16



E17



E24



E25



E26




E27



E28



E29



E30

