

# FLUORESCENT LAMP HOLDERS

FLUORESCENT LAMP HOLDERS



**RAPID-START LAMP HOLDER**  
 MOLDED IN WHITE  
 THERMOSETTING PLASTIC  
 Wireways for Flush Wiring Holes  
 Centered 31/32"  
 9" 18 GA. 105° Leads  
 Rated 660W-600V

**D2653**



**RAPID-START LAMP HOLDER**  
 SNAP-IN ONLY  
 DIAMETER HOLES .156"  
 PANEL THICKNESS  
 .033 TO .054mm  
 9" 18 GA. 105° Leads  
 Rated 660W-600V

**D3945**



**AUTOMATIC LOCKING & EJECTION**  
 BI-PIN LAMP HOLDERS  
 MOLDED OF WHITE THERMOSETTING PLASTIC  
 STEEL MOUNTING BRACKET RIVETED TO BODY  
 HOLE THREADED #6-32 AND LOCATED 11/16" ON  
 CENTER FROM BACK OF LAMP HOLDER  
 6" 18 GA. 105° Leads  
 Rated 660W-250V

**D2669** Left Hand Side **D2668** Right Hand Side



**RAPID START LAMP HOLDERS**  
 MOLDED WHITE BODY  
 COPPER ALLOY CONTACTS  
 Wireways for Flush Mounting  
 9" 18 GA. 105° Leads  
 Rated 660W-600V

**D2760** Rigid End **D2762** Plunger End



**SINGLE LAMP HOLDER**

**D486**

**LAMP HOLDER AND  
 STARTER BASE**

**D485**



**TWIN-BUTT ON BI-PIN  
 LAMP HOLDER**  
 PRESSURE LOCK TERMINALS  
 QUICKWIRE SINGLE SCREW  
 Butt on mounting with  
 2 screw holes  
 Rated 660W-600V

**D3947**