



FEATURES¹


Equivalent Source	65W Halogen
L70 lumen depreciation design criteria	50,000 hours
Housing	Aluminum
Socket	E26
Operating Temperature	-20°C to +40°C
E26 MOL	3.74in, 111.5mm
Voltage	120 VAC
Weight	.99 lbs, 450g
Power Factor	≥.9
Warranty	5 year limited

MyNature Coastal

Benefits

Certified by the Florida Fish & Wildlife Conservation Commission (FWC), this proprietary LED source is optimized to be less disruptive to nesting and hatching sea turtles.

- Patented spectrum does not disturb wildlife.
- Regular light bulbs disturb sea turtles.
- Replaces your white lights during hatching season.



Specifications supplied are nominal. Please refer to the DOE's Lighting Facts Tolerance Guidelines. ¹ Values are nominal, advances from further innovation, specifications are subject to change.

SPECIFICATIONS

Part Number	Base Type	Wattage	Lumens	Voltage	ССТ	Spectrum
DFN 30SN AM FL 120	E26	13W	125	120	1500K	>590nm

ORDERING INFORMATION \\ DFN 30SN AM FL 120

DFN Definity 30SN 30 Short Neck AM MyNature Coastal FL Flood 120 120 Volt	Family	Product	Color (CCT	olor (CCT)		ution	Voltage
CERTIFICATIONS THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXITS. NOT FOR USE IN TOTALLY ENCLOSED FIXTURES, PERFORMANCE MAY DECLINE DUE TO TYPE OF FIXTURE ENCLOSUBE: CAUTION: RISK OF SHOCK - DO NOT USE WHERE DIRECTLY EXPOSED TO WATER. TURN, OF POWER BEFORE INSPECTION, INSTALLATION, OR REMOVAL. DO NOT OPEN - NO USER SERVICEABLE PARTS INSIDE. Suitable for damp locations. Use and has been tested and found to comply with the limits for a class B digita dive. These limits are designed to provide reasonable with part 15 of the FOC rules and has been tested and found to comply with the limits for a class B digita direquency pergy and, if not installed and used in accordance with the instructions, may cause barmed interference to radio communications. Any changes or modifications not expressly approved by the	DFN Definity	30SN 30 Short Neck	AM	MyNature Coastal	FL	Flood	120 120 Volt
CERTIFICATIONS THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXITS. NOT FOR USE IN TOTALLY ENCLOSED FIXTURES, PERFORMANCE MAY DECLINE DUE TO TYPE OF FIXTURE ENCLOSUBE: CAUTION: RISK OF SHOCK - DO NOT USE WHERE DIRECTLY EXPOSED TO WATER. TURN, OF POWER BEFORE INSPECTION, INSTALLATION, OR REMOVAL. DO NOT OPEN - NO USER SERVICEABLE PARTS INSIDE. Suitable for damp locations. Use and has been tested and found to comply with the limits for a class B digita dive. These limits are designed to provide reasonable with part 15 of the FOC rules and has been tested and found to comply with the limits for a class B digita direquency pergy and, if not installed and used in accordance with the instructions, may cause barmed interference to radio communications. Any changes or modifications not expressly approved by the							
CERTIFICATIONS THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXITS. NOT FOR USE IN TOTALLY ENCLOSED FIXTURES, PERFORMANCE MAY DECLINE DUE TO TYPE OF FIXTURE ENCLOSUBE: CAUTION: RISK OF SHOCK - DO NOT USE WHERE DIRECTLY EXPOSED TO WATER. TURN, OF POWER BEFORE INSPECTION, INSTALLATION, OR REMOVAL. DO NOT OPEN - NO USER SERVICEABLE PARTS INSIDE. Suitable for damp locations. Use and has been tested and found to comply with the limits for a class B digita dive. These limits are designed to provide reasonable with part 15 of the FOC rules and has been tested and found to comply with the limits for a class B digita direquency pergy and, if not installed and used in accordance with the instructions, may cause barmed interference to radio communications. Any changes or modifications not expressly approved by the							
CERTIFICATIONS THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXITS. NOT FOR USE IN TOTALLY ENCLOSED FIXTURES, PERFORMANCE MAY DECLINE DUE TO TYPE OF FIXTURE ENCLOSUBE: CAUTION: RISK OF SHOCK - DO NOT USE WHERE DIRECTLY EXPOSED TO WATER. TURN, OF POWER BEFORE INSPECTION, INSTALLATION, OR REMOVAL. DO NOT OPEN - NO USER SERVICEABLE PARTS INSIDE. Suitable for damp locations. Use and has been tested and found to comply with the limits for a class B digita dive. These limits are designed to provide reasonable with part 15 of the FOC rules and has been tested and found to comply with the limits for a class B digita direquency pergy and, if not installed and used in accordance with the instructions, may cause barmed interference to radio communications. Any changes or modifications not expressly approved by the							
		CERTIFICATIONS THIS DEVICE IS NOT IN OF PATURE ENCLOSE OF PATURE ENCLOSE OF REMOVAL DO NOT With part 15 of the FCC DAMP protection against har used in accordance wi			SURE. CAUTION: RISK OF SHOCK - DO NOT USE WHERE DIRECTLY EXPOSED TO WATER, TURN OFF POWRE BEFORE INSPECTION, INSTALLATION, IOT OPEN - NO USER SERVICEABLE PARTS INSIDE. Suitable for damp locations. Use only on 120 volt, 60 Hz circuits. This device complies CC rules and has been tested and found to comply with the limits for a class B digital device. These limits are designed to provide reasonable narmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the		



Specifications are typical values and may change without notification. ©2013 Lighting Science Group Corporation. All rights reserved.