

# OMNIDRIVE® X DIMMABLE DRIVER

Versatile driver for most high-performance dimming applications. Reduce complexity with universal input voltage and multiple dimming protocols in a single driver.



## FEATURES & BENEFITS

- ELV, Triac, and 0-10V dimming in a single driver
- 110-277VAC universal input
- No minimum load
- Minimum dimming level of <1%, depending on dimmer
- UL Listed and Title 24 compliant

## QUICK SPECS

Environment	Indoor / Outdoor
Input Voltage	110-277VAC
Output Voltage	12VDC & 24VDC models
Connection Type	Hardwired
Warranty	5-Year Limited Warranty
Dimming	Forward Phase, Reverse Phase Dimming, and 0-10V Dimming
Certification	UL Listed & JA8 / JA10 Compliant

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

## 24V OMNIDRIVE® X

OUTPUT	SKU	WATTAGE	CLASS 2	ENVIRONMENT	DIMENSIONS W/O J-BOX	DIMENSIONS W/ J-BOX (-J)
<b>24 VDC</b>	DI-ODX-24V30W(-J)	30W	Yes	Indoor / Outdoor	2.1 × 0.8 × 6.1 in.	3.7 × 1.36 × 6.5 in.
	DI-ODX-24V60W(-J)	60W	Yes	Indoor / Outdoor	2.4 × 1 × 7 in.	3.7 × 1.36 × 7.4 in.
	DI-ODX-24V96W(-J)	96W	Yes	Indoor / Outdoor	2.7 × 1.7 × 9 in.	3.7 × 1.36 × 8.66 in.
	DI-ODX-24V120W-J	120W	No	Indoor / Outdoor	—	3.7 × 1.36 × 8.66 in.
	DI-ODX-24V200W-J	200W	No	Indoor / Outdoor	—	4.92 × 1.95 × 10.24 in.

## 12V OMNIDRIVE® X

OUTPUT	SKU	WATTAGE	CLASS 2	ENVIRONMENT	DIMENSIONS W/O J-BOX	DIMENSIONS W/ J-BOX (-J)
<b>12 VDC</b>	DI-ODX-12V30W(-J)	30W	Yes	Indoor / Outdoor	2.1 × 0.8 × 6.1 in.	3.7 × 1.36 × 6.5 in.
	DI-ODX-12V60W(-J)	60W	Yes	Indoor / Outdoor	2.4 × 1 × 7 in.	3.7 × 1.36 × 7.4 in.
	DI-ODX-12V100W-J	100W	No	Indoor / Outdoor	—	3.7 × 1.36 × 8.66 in.
	DI-ODX-12V120W-J	120W	No	Indoor / Outdoor	—	3.7 × 1.36 × 8.66 in.
	DI-ODX-12V200W-J	200W	No	Indoor / Outdoor	—	4.92 × 1.95 × 10.24 in.