

PROTWIST DETACHABLES

DR3W

(26 / 32 / 42W)

D: 2-1/2" x H: 3-1/8", 1/8 IP hickey and 24" leads. Can be used with: table, floor, sconces, ceiling, outdoor, pendant, new & retrofit lamps



DR2632D

Dimmable (26 / 32W)

D: 3-5/8" x H: 3-1/4", 1/8 IP hickey and 36" leads, no saddle needed. Ivory, 120V-60HZ, UL & C-UL, indoor/outdoor-minus 20 degrees, replaceable ballast, detachable-twist lock



A. DR13-13W

B. DR18-18W

C. DR26-26W

D: 1-3/4" x H: 2-7/8", 1/8 IP hickey and 24" leads. Can be used with: table, floor, sconces, ceiling, outdoor, pendant, new & retrofit lamps



A. DR13LP (13W Low Profile)

B. DR18LP (18W Low Profile)

C. DR26LP (26W Low Profile)

D: 1-3/4" x H: 2-7/8" Ring 2", 1/8 IP hickey and 36" leads. Threaded case can be used for pendant fixtures



A. DR13UR (13W UNO / Ring)

B. DR18UR (18W UNO / Ring)

C. DR26UR (26W UNO / Ring)

D: 1-3/4" x H: 2-7/8" Ring 2", 1/8 IP hickey and 36" leads. Threaded case can be used for pendant fixtures



A. DR13SIB (13W Snap-In Bracket)

B. DR18SIB (18W Snap-In Bracket)

D: 2-1/2" x H: 3-1/8", 1/8 IP hickey and 24" leads. Can be used with: table, floor, sconces, ceiling, outdoor, pendant, new & retrofit lamps



DR21

With Ring U-Channel 1/8 IP hickey, 24" 18AWm 105° Leads, W/24" ground wire attached PTH



DR14

U-Channel 1/8 IP Hickey 24" 18AWM 105° Leads



DR17

U-Channel 1/8 IP Hickey With screw terminals



DR15

1/8 IP Hickey 24" 18AWM 105° Leads



DR20

Side Mount 1/8 IP Hickey 24" 18AWM 105° Leads

