

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Compatible with RAB Type C T8 LED Lamps only
- Meets FCC Part 15 (Class B) Consumer Limits
- Short Circuit Overload and Open Load Protection
- Suitable for Dry and Damp Locations
- UL8750 Recognized Component
- Dimmable with 0-10V Dimmer
- Maximum Case Temperature: 75°C/167°F
- Input Frequency: 50/60 Hz
- THD: < 20%
- Type P
- Output Class 2

Technical Specifications		Other
Electrical	Efficiency: >85%	Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
THD: <20%	Operating Temperature: -20°C/-4°F to 45°C/113°F	
Power Factor: >0.9	Dimming: 0-10V Dimming	
Input Voltage: 120-277V AC	Construction	
Input Frequency: 50/60 Hz	Storage Temperature: -30°C/-22°F to 80°C/176°F	
Input Power (Max): 52W	Protection: Open circuit protection, over voltage protection, short circuit protection	
Max. Standby Power: 1W	Reduced Lamp Load: Parallel output for each channel, support N and N-1 application	
Output Current: 260mA*4	Compliance	
Max Output Voltage: 30-45V	Certifications: Class P, UL8750, Output Class 2	
No-Load Voltage: 56V dc Max.		

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.7	9.8	10
PALLET	768	38.9	39.8	43.1

Dimension

