

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Illuminates entire LED load at reduced output under emergency mode
- One Piece Design with Metal Housing
- 2-in-1 LED test switch and indicator light included
- Evaluated to UL 924 requirements
- Not for use with dimmers
- 90 Minute operation in Emergency Mode
- UL Listed
- Operating Temperature: 32°F/0°C to 122°F/50°C

Technical Specifications		
<p>Performance</p> <p>Product Type: Driver</p> <p>Input Wattage: 5W</p> <p>Construction</p> <p>Material: Metal Casing</p> <p>Electrical</p> <p>Power Factor: >0.4 @ 120V</p> <p>Input Voltage: 120-277V AC</p> <p>Operating Frequency: 50/60Hz</p> <p>Input Current @ 120V: 100mA</p> <p>Rated Output Current: Load Dependent</p>	<p>Max Output Voltage: 300VDC</p> <p>Installation</p> <p>Installation Type: Emergency Back up for Double Ended or Single + Double ended tubes</p> <p>Compliance</p> <p>UL Listed: Yes</p> <p>NSF Listed: Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.</p> <p>California Energy Commission (CEC) Status: Lawful for Sales in California</p>	<p>Other</p> <p>5-Year, No-Compromise Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.</p>

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	13.6	10.6	8
PALLET	1500	45.3	39.4	49.2

Dimension

